

FIRST RE-ESTABLISHMENT

GCDB 400600

Corner to Sections 3, 4, 9 and 10, Township 35 South, Range 2 West, W.M.

Found the original pine BT to the Southeast down with scribe legible; the black oak BT to Southwest with scribe visible, stump hole of the fir BT to the Northwest and the remains of the decayed black oak to the northeast; also found a mound of stone to mark the corner;

From which evidence

- Set a 2" x 36" galvanized iron pipe 30" in the ground for corner

From which:

- A 6" fir scribed C.S. - BT bears S.15°W. 15 feet,
- Scribe a 12" laurel C.S. - BT bears N.4°W. 12 feet,
- Scribed a 6" fir C.S. - BT which bears N.57°E. 18.8 feet,
- Scribed a 20" black oak C.S. - BT which bears S.68°E. 19.3 feet.

March 1, 1952
C. Z. Boyden
M.E. Boyden

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 400600

Section common to Sections 3, 4, 9, and 10, Township 35 South, Range 2 West, W.M. V = 17½

Found, projecting 4 ins. in mound of stone, the 2 ins. diam. G.I. pipe set on first re-establishment (page 19) in 1952. Inside found pipe I set a 1 x 36 ins. G.I. pipe, 30 ins. in the ground with a 2½ ins. bronze disc marked:

JACKSON COUNTY 1979

T35S R2W

4	3
9	10

From which reference trees recorded on first re-establishment found as follows:

- Fir, 10 ins. diam., with healed blazes, brs. Record: N57E, 18.8 feet to estimated face. Re-measured 19.05 feet to center of tree. The base and root hole of a down (tipped over) black oak 22 ins. diam., scribed "CS" brs. Record: S68E, 19.3 feet.
- Fir stob, 9 ins. diam. with healed blazes, brs. Record: S15W, 15.0 feet to estimated lower face.
- Laurel, 16 ins. diam., containing scribe marks in partially exposed lower face, brs. Record: N4W, 12.0 feet to scribed lower face. Re-measured 12.45 feet to center of tree.

Original bearing trees recorded by Ives and Hyde in 1854 found as follows:

- Black Oak shell (living) 16 ins. diam., brs. Record: N10E, 39.60 feet to estimated lower face.
- The root hole of a down and rotted pine scribed "R2W T35S 10 BT" brs. Record: S48E, 7.26 feet.
- Black oak, 19 ins. diam. with axed and/or rotted out faces brs. S66½W, 18.48 feet to estimated lower face. Record: S68W, 18.48 feet.
- Stump hole found as record location of original Northwest Bearing Tree.

I mk. new trees CS BT and take measurements to center of trees at lower blaze:

- Laurel, 8 ins. diam., brs. S2E, 50.35 feet White Oak, 17 ins. diam., brs. S80W, 113.89 feet

Corner lies at top (near point) of Northeast ridge, about 365 feet East of location marker on 6 ins. diam. white oak, alongside dirt road.

J. Swanson
R. Frost
June 7, 1979

Approved by: Edward McGinty
County Surveyor


SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 400600

Section corner common to Sections 3, 4, 9 and 10, Township 35 South, Range 2 West, W.M.

Found exposed 6 ins. and in a mound of stones, the 1 in. diam. galvanized iron pipe set inside a 2 ins. diam. galvanized iron pipe on Second Re-establishment in 1979. 2½ ins. diam. brass cap set in 1979 now gone. Cemented in top of said 1 in., diam. pipe a 2½ ins. diam. brass cap, marked:



Bearing trees recorded on Second Re-establishment in 1979, found and measured to center of tree at lower blaze:

Trees recorded by Ives and Hyde in 1854

- Black Oak shell, now 17 ins. diam. brs. N10°E, 40.0 ft Record: 39.60 feet to face of lower blaze.
- Black Oak, now 20 ins. diam. with rotted out faces brs. S66½°W, 19.1 feet. Record: S68°W, 18.48 feet to face of lower blaze.

First Re-establishment in 1952

- Dead fir, now 10 ins. diam. with healed blazes brs. Record: N57°E, 19.05 feet.
- Laurel, now 20 ins. diam. with healed blazes brs. Record: N4°W, 12.45 feet.

Second Re-establishment in 1979

- Laurel, now 9 ins. diam. with partially healed upper blaze brs. Record: S2°E, 50.35 feet.
- White Oak, now 19 ins. diam. with healed blazes brs. Record: S80°W, 113.89 feet.

Corner lies near top of ridge and approximately 0.5 feet East of east end of new fence.

June 10, 2002
H. Durkee
T. Newcomb

Roger Roberts
Jackson County Surveyor

P. -130
V. -16°