

## FIRST RE-ESTABLISHMENT

### GCDB 400700

Section corner common to Sections 3 and 4, Township 35 South, Range 2 West, and Sections 33 and 34, Township 34 South, Range 2 West, W.M.

Found  $\frac{5}{8}$ -inch rebar as set on Recorded Survey No. 3468

From which:

- Original Southeast bearing tree, now a 23 ins. Black Oak with scribe visible brs. S15°E, 129.0 feet to face of lower blaze. Record: 128.7 feet.
- Stump holes of original bearing trees to the Northwest and Northeast check with record Northeast bearing tree, Pine, found on ground with scribing visible.

Set a 1 x 36 ins. galvanized iron pipe, 33 ins. in the ground over said pin with a 2½ ins. diam. brass cap stamped:

T34S-35SR2W	
33	34
Section	Cor.
4	3
C.S.	
1971	

From which trees marked by LS 505 found; distances to nail and shiner in face:

- 14 ins. diam. Pine, brs. S10¾°W, 25.5 feet.
- 9 ins. diam. Pine, brs. N53°W, 31.7 feet.
- 10 ins. diam. Laurel, brs. N41¾°E, 31.4 feet.

August 12, 1971  
Gary Kaiser  
Lloyd Shreeve


**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 400700

Section corner common to Sections 3 and 4, Township 35 South, Range 2 West, and Sections 33 and 34, Township 34 South, Range 2 West, W.M.

Found projecting 4 ins., the 1 x 36 ins. galvanized iron pipe set on first re-establishment with brass cap marked:



Original bearing tree marked by Ives and Hyde in 1854 found:

- Black Oak snag, now 24 ins. diam. with rotted lower face, brs. Record: S15°E, 128.7 feet to estimated face.

Bearing trees marked on survey No. 3468 in 1967 found and Re-measured to center of trees at lower blazes:

- Madrone, now 13 ins. diam., with partial scribe marks visible in partially healed double blazes, brs. Record: N41 $\frac{3}{4}$ °E, 32.08 feet.
- Yellow Pine, now 17 ins. diam. with scribe marks visible in partially healed double blazes, brs. S10 $\frac{1}{4}$ °W, 25.40 feet. Record: S10°50'30"W.
- Yellow Pine, now 13 ins. diam. with healed double blazes, brs. N51 $\frac{1}{2}$ °W, 32.02 feet Record: N53°07'30"W.

Take new reference as follows:

- White Oak, 6 ins. diam. with double blaze, but unscribed, brs. S66 $\frac{1}{2}$ °E, 20.45 feet to center of tree at lower blaze.

Corner lies on a S30°W, rounded ridge top, 10 feet East and 13 feet South of a wandering wire fence line, with blazed and painted lines bearing North and West from corner.

December 4, 1986  
R. Romio  
D. Edwards

Edward McGinty  
County Surveyor

V = 18 $\frac{3}{4}$ °  
P. 345-346