


## FIRST RE-ESTABLISHMENT

GCDB 440520

Center- South One- Sixteenth corner of Section10, Township 35 South, Range 2 West, W.M.

Found  $\frac{5}{8}$  in. diam. pin set on Filed Survey 4149, dated 1969, 12 ins. deep. Set a 1x12 ins. galvanized iron pipe with  $2\frac{1}{2}$  ins. diam. brass cap marked;



Flush with road surface.

Bearing trees marked on Filed Survey 4149 found;

- Black Oak 13 ins. diam., with scribe marks 'S10' visible on axed open face, brs. N66°30'W, 48.5 ft. to face of upper blaze. Record distance 48.7 ft.
- White Oak 10 ins. diam., with scribe marks visible on axed open face, brs. S60°W, 56.3 ft. Record distance 56.6 ft.

Set new references,  $\frac{5}{8}$  x 24 ins. rebar with 2 ins. diam. aluminum caps marked JACKSON COUNTY SURVEYOR, flush with the ground surface;

- Located on the East side of Meadows Rd., 5 ft. East of the edge of pavement, brs. N47°56'18"E, 35.38 ft.
- Located on the East side of Meadows Rd., 5 ft. East of the edge of pavement, brs. S38°46'25"E, 39.34 ft.

Corner is located in the south bound lane of Meadows Rd.

September 4, 2013  
S. Beecher  
S. Fein  
O. Ribansky

Scott D. Fein  
Jackson County Surveyor

P. - 16