

FIRST RE-ESTABLISHMENT

GCDB 500300

Corner to Sections 22, 23, 26 and 27, Township 35 South, Range 2 West, W.M.

Found a 6" x 8" x 14" stone with X on top for corner; also original BT, a 36" white oak, with scribe visible which bears N. 75°W., 295.7 feet.

Set a 2" x 36" galvanized iron pipe 18" below the surface of the ground for corner at the exact location of the above mentioned stone with X; also replaced the stone in its original position, from which;

- A 9" white oak scribed C.S.-BT bears S.55½°W., 732.3 feet.
- Scribed a 12" white oak C.S.-BT which bears N.15¾°W., 159.6 feet.
- Scribed a 24" white oak C.S.-BT which bears N.7¼°E., 217.8 feet.
- No tree near in the southeast quadrant.

December 18, 1944
C. Z. Boyden
R. E. Welch
L. J. Shorey

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500300

Section corner common to Sections 22, 23, 26, and 27, Township 35 South, Range 2 West, W.M.
 $V = 20^\circ$

Found, 13 ins. deep, the 2 ins. diam. iron pipe under the 13 x 7 x 8 ins. stone mkd; with cross (both ends) set on first re-establishment, page 12, in 1944.

Inside said pipe I set a 1x36 ins. G.I. pipe, 3 ins. below the surface of the ground with a 2½ ins. bronze disc marked:

| | |
|---------------------|----|
| JACKSON COUNTY 1979 | |
| T35S R2W | |
| 22 | 23 |
| ----- | |
| 27 | 26 |

Reference trees marked on first re-establishment found as follows:

- The south branch, 25 ins. diam. of a double White Oak, with healed blazes, brs. $N7^\circ 15'E$, 218.65 feet, to center of tree at upper blaze. Record: $N7\frac{1}{4}^\circ E$, 217.8 feet.
- Sawed and rotted White Oak stump, 12 ins. diam., brs. $N14^\circ 42'W$, 160.0 feet to center of tree. Record: $N15\frac{3}{4}^\circ W$, 159.6 feet.
- The single original bearing tree recorded by Ives and Hyde in 1854, a White Oak, now 44 ins. diam., with healed blazes, brs. $N75^\circ W$, 295.4 feet to center of tree. Record: $N74^\circ W$, 295.68 feet.

I set $\frac{5}{8}$ x 30 ins. re-steel rods, flush with the surface of the ground with yellow plastic caps marked: "JACKSON C.S." as follows:

- At the base of a 6 ins. diam. Hawthorn Tree, the corner of South-East bearing fence lines. Re-bar brs. $S45^\circ 03'E$, 28.92 feet.
- At the base of wood post corner of North-South and West bearing fence lines. Re-bar brs. $N45^\circ 46'E$, 29.07 feet.

Corner lies at the P.I. of South and East bearing farm roads, about 22 feet $S82^\circ W$ from location marker on road gateway fence post.

June 20, 1979
J. Swanson
R. Frost
J. Gallegos

Approved by: Edward McGinty
County Surveyor