

FIRST RE-ESTABLISHMENT

GCDB 500440

Quarter corner common to Sections 14 and 15, Township 35 South, Range 2 West, W.M.

Found the original witness tree to the NE with scribe marks plain. Also found the stump of the original SW witness tree.

Set a 1" x 36" galvanized iron pipe 34" in the ground for corner from which:

- The original witness tree (now a 30" Y. pine bears N.12°E., 103.6 feet;
- The original witness tree (now a 36" Y. pine stump) the center of which bears S.82½°W., 121.5 feet;

I mark new trees as follows:

- A 9" White Oak scribed CS-BT bears S 84°W. 102.4 feet;
- A 10" White Oak, scribed CS-BT bears S 15½°E, 26.3 feet.

August 10, 1960
Mark E. Boyden
F.A. Roberts
Claude Masters, present

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500440

Quarter corner common to Sections 14 and 15, Township 35 South, Range 2 West, W.M.

Found projecting 2 ins., the 1 ins. diam. iron pipe reported set on first re-establishment, page 20, in 1960. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T35S R2W
¼S
15 | 14
C.S.
1988

Original bearing tree marked by Ives and Hyde in 1854 found:

- Pine snag, 29 ins. diam. with scribe marks including "¼" visible on opened face, brs.
Record: N12°E, 103.80 feet to said face. Original record distance; 103.62 feet.

Bearing trees marked on said first re-establishment found with double healed blazes and measured to center of trees at lower blaze:

- White Oak, now 14 ins. diam., brs. S15°E, 26.67 feet. Record: S15½°E, 26.3 feet.
- White Oak, now 11 ins. diam., brs. Record: S84°W, 102.75 feet. Record distance; 102.4 feet.

Corner lies in brushy openings, 1.6 feet North of a large Pine corner post to fences bearing North, South, East and West.

April 28, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 18¾°

P.-175