

## FIRST RE-ESTABLISHMENT

GCDB 500540

Quarter corner Sections 10 and 11 Township 35 South, Range 2 West.

Found remains of a yellow pine, consisting of some bark and the burned out hole, at which point residents testified the yellow pine bearing tree stood.

Set harrow tooth flush with the ground for corner 1 link West of the location of the circumference of the original tree as near as possible to judge.

From this point so set, measured west 13 links to the stump of small black oak, making the point so set and marked with the harrow tooth check the field notes.

Blazed and marked two new bearing trees as follows:

- A 12" black oak bears S.66°E., 18.6 feet.
- A 16" yellow pine bears N.29½ W., 48.1 feet.

June 10, 1914  
A.T. Brown, Dept. County Surveyor  
Fred Schapleigh, Lansing and Sweet (present.)

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 500540

Quarter Corner to Sections 10 and 11, Township 35 South, Range 2 West, W.M.

### Found

- ¾" iron pipe at corner,
- Also re-established 18" yellow pine N30°W, 48.1 feet,
- Also black oak stump of BT to southeast as reported by Surveyor A.T. Brown in his re-establishment June 10, 1914;

From the ¾" iron pipe as found for corner

- Established a new tree, a 20" black oak, scribed C.S.-BT which bears S.12°W., 21.4 feet.

September 5, 1944  
C. Z. Boyden  
B. L. Campbell  
L. J. Shorey

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

## THIRD RE-ESTABLISHMENT

GCDB 500540

Quarter corner common to Sections 10 and 11, Township 35 South, Range 2 West.

The corner monument and bearing trees have been destroyed by road relocation. Determined the location for the corner from temporary references set by the County Road Department survey crew on March 10, 1964 when the pipe corner was in evidence.

Set a 1" x 24" galvanized iron pipe with 2½" bronze cap with top 3" below the surface of the county road for corner. Said cap stamped:

T35S R2W  
¼ 10 | 11 c.s.  
1965

From which:

- Set a ¾" x 24" iron pin North 30.0 feet;
- Set a ¾" x 24" iron pin South 30.0 feet;
- A 12" Yellow Pine scribed "CS-BT" bears South 33° East, 43.4 feet to the face of the upper blaze.

December 6, 1965  
L. D. Pinkham, Deputy County Surveyor  
Lloyd Hart

SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT

## FOURTH RE-ESTABLISHMENT

GCDB 500540

One-Quarter corner common to Sections 10 and 11, Township 35 South, Range 2 West, W.M.  
 $V = 19^\circ$

Found, 1 ins. below surface of gravel road, the 1 ins. diam. G.I. pipe with 2½ ins. diam. brass cap marked:

T35S R2W  
¼ 10 | 11 CS  
1965

As recorded on third re-establishment, page 26, in 1965. Said monument found disturbed, 0.04 feet South of the original position.

Place said pipe and cap in original position and secure with cement. From which found at record locations, the ¾ ins. diam. iron pins set on above re-establishment:

- North, 30.0 feet projecting 2 ins.
- South, 30.0 feet projecting 1 ins. located 1.5 feet West of intersection of East-West and South brg. fence lines.
- Ponderosa Pine, 14 ins. diam. with healed blazes, marked on same re-establishment, brs.  $S32^\circ 13'E$ , 43.9 feet to center of tree at lower blaze. Record,  $S33^\circ E$ , 43.4 feet.
- Found flush, a ⅝ ins. diam. rebar, reportedly set by Jackson County Road Dept., brs. South, 47.68 feet. On top of which set a yellow plastic cap marked: "JACKSON C.S."

Set ⅝ x 30 ins. rebars with yellow plastic cap marked: "JACKSON C.S.":

- $N61^\circ 30'E$ , 62.87 feet projecting 2 ins.
- $N52^\circ 35'W$ , 52.27 feet projecting 1 ins. at intersection of West and Northeast brg. fence lines.

Corner lies in middle of Sweet Road (course; East-West) about 816 feet West of intersection of Antioch and Sweet Roads.

September 29, 1980

R. Frost  
J. Gallegos

Edward McGinty  
County Surveyor

P.-193