

FIRST RE-ESTABLISHMENT

GCDB 500700

Section corner common to Sections 34 and 35, Township 34 South, Range 2 West and Sections 2 and 3, Township 35 South, Range 2 West, W.M.

In a found 1 ins. diam. pipe hole in a mound of stones, set a 1x36 ins. galvanized iron pipe 30 ins. in the ground. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T34S R2W	
34	35
— —	
3	2
T35S	
C.S.	
1988	

Scribe trees "CS-BT" and measure to center of trees at lower blaze:

- White Oak, 7 ins. diam., brs. N67°E, 14.41 feet.
- White Oak, 5 ins. diam., brs. S55°E, 36.90 feet.
- White Oak, 12 ins. diam., with lower face area chopped out but scribed "CS" on upper blaze, brs. S67°W, 18.18 feet. Record per recorded Survey No. 4000; S65°40'20"W, 17.83 feet to face.
- White Oak, 10 ins. diam., brs. N32°W, 40.74 feet.

Corner lies on a 15%, N40°E slope and 12 feet West and 10 feet South of a tree corner post to fences North, South and East and 3 feet North of an East-West fence.

January 20, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 19°
P. -10