

FIRST RE-ESTABLISHMENT

GCDB 540200

One-Quarter corner common to Sections 26 and 35, Township 35 South, Range 2 West, W.M.
 $V = 19\frac{1}{2}^\circ$

Found, $\frac{5}{8} \times 24$ ins. re-steel rod on North-South fence line in mound of stone projecting 16 ins. as established on record survey No. 5401 by William Eimstad in 1973.

I replace said rod with a 2x30 ins. G.I. pipe with flanged end projecting 15 ins. and $2\frac{1}{2}$ ins. diam. brass cap marked:

T35S R2W
26
 $\frac{1}{4}$ S —
35
CS
1979

From which, I find the bearing tree established by the above survey.

- White Oak, 10 ins. diam., scribed " $\frac{1}{4}$ S 35 BT" in exposed single face, brs. $S37^\circ E$, 26.65 feet to scribed face. Record: $S38^\circ E$, 26.65 feet.

I found the original bearing trees recorded by Ives and Hyde in 1854 and take measurements to center of trees at lower blaze:

- White Oak, 25 ins. diam. with axed and rotted faces brs. $S87^\circ W$, 206.41 feet. Record: $S87^\circ W$, 206.58 feet.
- White Oak, 21 ins. diam., with axed and rotted faces brs. $N21^\circ W$, 295.02 feet. Record: $N21\frac{1}{4}^\circ W$, 295.02 feet.

I mark "CS" "BT":

- White Oak, 9 ins. diam., brs. $N69^\circ 38' W$, 167.0 feet to center of tree, lower blaze.

I deposit found rod alongside corner and place location marker on yew wood fence post which lies alongside road, course $S75^\circ W$. Corner is ± 1925 feet South of location marker.

June 18, 1979

R. Frost
J. Gallegos

Approved by: Edward McGinty
County Surveyor