

**PROPORTIONED CORNER**

**GCDB 540300**

Quarter Corner to Sections 23 and 26, Township 35 South, Range 2 West, W.M.

No evidence of original corner.

Set a 1" x 36" galvanized iron pipe 8" below the surface of the ground for corner on single proportional distance from the section corner to the east and west,

From which:

- A 15" white oak scribed C.S.-BT bears N.74½°W., 241.3 feet.
- Scribed a 12" white oak C.S.-BT which bears N.55½°E., 553.6 feet.

December 19, 1944  
C. Z. Boyden  
R. E. Welch  
L. J. Shorey

**SEE NEXT PAGE FOR FIRST RE-ESTABLISHMENT**

## FIRST RE-ESTABLISHMENT

GCDB 540300

Quarter corner common to Sections 23 and 26, Township 35 South, Range 2 West, W.M.

Found 10 ins. deep, the  $\frac{5}{8}$  ins. diam. rebar, set on Survey No. 3948 in 1969. Alongside said pin is found the 4x6x10 ins. stone, marked with chiseled cross, reported in 1969, to be that stone described on \* 1910 survey by A.T. Brown.

Charcoal particles were also found as reported on Survey No. 3948. The original corner monument recorded by Ives & Hyde in 1854 was a "charred stake".

Directly over the found rebar, set a 1x36 ins. galvanized iron pipe, with 2½ ins. diam. brass cap marked:

T35S R2W  
23  
¼S —  
26  
C.S.  
1989

**Note:** The original record indicates no bearing trees were marked and no record of subsequent references to this position is found.

Set new references;  $\frac{5}{8}$  x 24 ins. rebars flush, with yellow plastic caps marked "Jackson C.S." brs:

- N4°51'E, 17.7 feet, located 5½ feet South of rail fence.
- S63°14'E, 37.57 feet, located 2½ feet North of the East post of gateway.

A 1 ins. diam. pipe, found 18 ins. deep, marking the proportionate position of subject corner as determined on 1944 (lost corner) re-establishment (page 10), brs. S4°51'W, 9.17 feet.

From said 1 ins. pipe, bearing trees marked in 1944 found and measured to center of tree(s) at lower blaze:

- White Oak, 19 ins. diam. with healed blazes, brs. N55°30'E, 553.85 feet. Record: 553.6 feet.
- White Oak, 21 ins. diam., with healed blazes, brs. N74°22'W, 241.88 feet. Record: N74½°W, 241.3 feet.

**See also Survey Numbers 1528 and 3452.**

Corner lies near middle of private road (C. West) to residence 13437 Antioch Road.

\* Reference; 1910 Road Survey, Book 3, page 45 and Ancient road surveys, Book 2, page 10.

January 3, 1989  
R. Frost, Tech.  
S. Beecher, Tech.

Verlyn Thomas  
County Surveyor

P.-2