

FIRST RE-ESTABLISHMENT

GCDB 540400

Quarter Section Corner to Sections 14 & 23, Township 35 South, Range 2 West.

Found stone with X on top in the County Road, the recognized corner, from which

- A 24" White Oak with old axe mark visible which tree is the recognized original bearing tree, and bears South 63° 15' East, 131.7 feet.
-

Lowered the above mentioned corner stone which is a 6" x 2" x 16" stone to a point 6" below the surface of the road for corner, from which

- A ¾" x 32" iron set 26" in the ground which bears west 28.0 feet.

August 20, 1930
C. Z. Boyden, Deputy County Surveyor
L. Pettegrew
D. King

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 540400

Quarter corner common to Sections 14 and 23, T35S R2W.

Found the 5" x 3" x ? sandstone with cross on top 4" below the road surface, and being 484.7 feet Southerly from the P.I. of Dodge Road at the centerline of Antioch Road. All of the RPs of the first renewal set by Deputy County Surveyor C. Z. Boyden on August 20, 1930 have been destroyed.

From said stone corner, I establish the following new references:

- A 14" White Oak, scribed "CS-BT" bears S39°E, 106.3 feet;
- A 12" White Oak, scribed "CS-BT" bears S6¾°W, 236.4 feet;
- Set a 5/8" x 24" iron pin which bears West 40.00 feet.

August 4, 1960
Mark E. Boyden
Deputy County Surveyor
F. A. Roberts

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 540400

One-Quarter corner common to Sections 14 and 23, Township 35 South, Range 2 West, W.M.

At the corner found, 8 ins. deep, beneath an unrecorded railroad spike a rebar, (See Survey No. 4235) ½ ins. diam., 20 ins. long. Origin unknown.

The marked stone monument noted on first re-establishment page 4, in 1930 was searched for to a depth of 30 ins. but not found.

Replace the above found rebar with a G.I. pipe, 1 ins. diam., 36 ins. long, set in concrete, flush with the asphalt road surface with 2½ ins. diam. bronze cap marked:

JACKSON COUNTY 1980
T35S R2W
14
¼S —
23

From which references recorded on above re-establishment found as follows:

- White Oak, 21 ins. diam., with scribe marks visible in partially exposed upper face, brs. S39°15'E, 106.80 feet to center of tree at lower blaze. Record: S39°E, 106.3 feet.
- Iron pin, 5/8 ins. diam., projecting 3 ins. in North-South brg. fence line, brs. Record: West, 40.0 feet.
- The Southwest bearing tree found down and moved by construction.

Set rebars, 5/8 ins. diam., 30 ins. long, flush with yellow plastic caps marked: "JACKSON C.S." located 0.5 feet East of North-South bearing fence line:

- S47°46'W, 53.05 feet.
- N47°35'W, 52.97 feet.

Corner lies in the middle of Antioch Road approximately 480 feet South of Dodge Road.

November 13, 1980
R. Frost
J. Gallegos
T. Connolly

Edward McGinty
County Surveyor

V = 19¾°

P. - 220