

FIRST RE-ESTABLISHMENT

GCDB 540600

One-Quarter Corner common to Sections 2 and 11, Township 35 South, Range 2 West, W.M.

Found projecting 3 ins. the $\frac{1}{2}$ ins. diam. iron pipe with pot metal cap set on recorded survey No. 4000 in 1969.

I remove said cap and drive a 1x36 ins. G.I. pipe over found $\frac{1}{2}$ ins. pipe, 34 ins. in the ground with $2\frac{1}{2}$ ins. bronze disc marked:

JACKSON COUNTY 1979
T35S R2W
2
 $\frac{1}{4}$ —
11

Reference trees recorded on above noted survey found as follows:

- Black Oak snag, 30 ins. diam., scribed " $\frac{1}{4}$ S11" in exposed single face, brs. $S72\frac{3}{4}^{\circ}E$, 30.62 feet to scribed face. Record: $S72^{\circ}43'E$, 30.62 feet.
- Fir snag, 16 ins. diam., scribed " $\frac{1}{4}$ S 2" in exposed single face, brs. $N38\frac{3}{4}W$, 8.39 feet to scribed face. Record: $N38^{\circ}39'W$, 8.39 feet.

I mound stones around corner, deposit found cap alongside and mark new trees "CS BT".

- Black Oak, 11 ins. diam., brs. $N17\frac{1}{2}^{\circ}E$, to center of tree at lower blaze, 44.77 feet to nail in westerly side of tree.
- Laurel, 10 ins. diam., brs. $S25^{\circ}W$, 28.20 feet to center of tree at lower blaze.

Corner lies an estimated 1250 feet west of location marker on wood post alongside Jones road and $N52^{\circ}W$, 12.6 feet from the center of 16 ins. diam. fir, the corner of North-South and East bearing fence lines.

June 5, 1979
J. Swanson
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 540600

Quarter corner common to Sections 2 and 11, Township 35 South, Range 2 West, W.M.

Found projecting 2 ins., the 2½ ins. diam. brass cap on a 1 ins. diam. iron pipe as described in first re-establishment, page 46, in 1979.

Bearing trees marked on Survey No. 4000 found:

- Black Oak snag, 30 ins. diam. with scribing visible on exposed single face, brs. S72°40'E, 30.7 feet to said face.
- Fir snag, 16 ins. diam. with scribing visible in exposed single face, bears N37°54'W, 9.00 feet to center of snag at base.

Bearing trees marked on said first re-establishment found and measured to center of tree at lower blaze:

- Black Oak stump, 11 ins. diam. with scribed "BT" visible, brs. N18°28'E, 44.8 feet to center at lower blaze.
- Madrone, 10 ins. diam. with scribing visible in partially healed double blazes, brs. S24°26'W, 28.07 feet to center at lower blaze.

Scribe a new tree "CS" "BT":

- Ponderosa Pine, 12 ins. diam., brs. N0°27'W, 26.40 feet to center of tree at lower blaze.

Corner lies on 30% Northeasterly slope in timber, in a small mound of stones and 12.6 feet N52°W, from the corner post to fences bearing North-South and East.

Bearings are based upon Survey No. 11096.

January 15, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

P.-15