

FIRST RE-ESTABLISHMENT

GCDB 540700

Quarter corner on Township line - Section 35, Township 34 South, Range 2 West & Section 2, Township 35 South, Range 2 West.

Found original BTs to Northeast and Southwest with scribe legible. Set a 1" x 36" galvanized iron pipe 34" in the ground for corner on record distance from both original BT`s which also checks the record course to the Northeast BT

- Scribed a 6" white oak CS-BT which bears N.79½°E., 63.2 feet.
- Scribed a 6" white oak CS-BT which bears S.15¼°W., 50.4 feet.

December 15, 1944.
C. Z. Boyden
R. E. Welch
L. J. Shorey

NOTE: 6/11/79

Set brass cap in iron pipe.

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 540700

Quarter corner common to Section 35 of Township 34 South, and Section 2 of Township 35 South, Range 2 West, W.M.

Found at corner position the 1 in. diam. galvanized iron pipe set in 1944 on First Re-establishment with the 2½ ins. diam. brass cap set by this office in 1979 bent over.

From the following evidence, replaced monument with a 2½ x 30 ins. galvanized iron pipe with a 3½ ins. diam. brass cap exposed 6 ins. in a mound of stones. Cap marked:

T34S R2W
¼ S35
•
S2
T35S
2006

Original bearing trees recorded by Ives and Hyde in 1854 found and measured to center at lower blaze:

- White Oak now 15 ins. diam. with healed double blazes brs. S36¾°W, 85.8 feet, record S38°W.
- White Oak with partially healed double blaze now 14 ins. diam. brs. N66°E, 80.7 feet. Record 81.2 feet.

Bearing trees set in 1944 on First Re-establishment found with healed double blazes measured to center at lower blaze:

- White Oak now 9 ins. diam. brs. N79½°E, 62.8 feet. Record: 63.2 feet.
- White Oak now 10 ins. diam. brs. Record: S15¼°W, 50.4 feet.

Corner lies approximately 15.5 feet easterly of north, south, and west of barbed wire fence corner.

August 22, 2006

B. Beeman

H. Durkee

Roger R. Roberts

Jackson County Surveyor

P. - 141

Nikon total-station