

FIRST RE-ESTABLISHMENT

GCDB 600400

Section corner common to Sections 13, 14, 23 and 24, Township 35 South, Range 2 West, W.M.

- Found the original White Oak bearing tree to the Southeast, opened the lower portion and found "BT" scribe.
- Also found the original White Oak bearing tree to the Southwest, opened the upper blaze and found scribe marks.
- Also found the original White Oak bearing tree to the Northeast with the inside rotted out.

For corner set a 1" x 36" galvanized iron pipe 35" in the ground with a 2½" bronze cap stamped:

T35S R2W	
Section Cor.	
14	13
----- C.S.	
23	24
1966	

From which, the original bearing tree now 26" White Oak bears South 65° East, 30.4 feet;

- The original bearing tree now 16" White Oak bears South 50° West, 29.7 feet;
- The original bearing tree now a 14" White Oak bears North 46° East, 44.4 feet;

Marked the following new trees:

- A 10" White Oak scribed "CS-BT" bears South 49° East,, 13.8 feet;
- A 16" White Oak scribed "CS-BT" bears North 7° West, 16.5 feet;
- An 18" White Oak scribed "CS-BT" bears North 47½° East, 93.7 feet.

August 1, 1966
Lee D. Pinkham, Deputy County Surveyor
Lloyd W. Hart

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 600400

Section corner common to Sections 13, 14, 23 and 24, Township 35 South, Range 2 West, W.M.

Found flush, the 1 ins. diam. galvanized iron pipe with 2½ ins. diam. brass cap marked:

T35S R2W	
Section Cor.	
14	13
23	24
1966	

c.s.

as described on First Re-Establishment, page 28, dated 1966.

Original bearing trees recorded by Ives & Hyde in 1854 and reported in 1966, found and measured to center of trees near base:

- White Oak, 16 ins. diam., with axed and rotted upper face, brs. N45°E, 45.1 feet. Record: N46°E, 44.1 feet.
- White Oak stump shell, about 24 ins. diam., brs. S65°E, 31.1 feet. Record: 30.4 feet.
- White Oak, 19 ins. diam., with axed and/or rotted upper face, brs. S50°W, 29.8 feet. Record: 29.7 feet.

Bearing trees marked in 1966 found with healed blazes and measured to center of trees at lower blaze.

- White Oak, 18 ins. diam., brs. N47½°E, 94.3 feet.
- White Oak, 13 ins. diam., brs. S50°E, 14.2 feet.
- White Oak, 18 ins. diam., brs. N7°W, 17.2 feet.

A found ½ ins. diam. rebar, protruding 1 ins. from a knob topped ¾ ins. diam. iron pipe, projecting 6 ins., brs. S66½°E, 3.55 feet.

Mark a new tree "CS" "BT"; White Oak, 16 ins. diam., brs. S21°W, 94.3 feet to center of tree at lower blaze.

Corner lies 18 ins. North of the (wood) post corner of 4-way fence line.

January 23, 1989
R. Frost, Tech.
S. Beecher, Tech.

Verlyn Thomas
County Surveyor

V = 17°
P.-40