

## PROPORTIONED CORNER

GCDB 600500

Corner to Sections 11, 12, 13 and 14, Township 35 South, Range 2 West.

No definite evidence of original corner.

Set a 2" x 24" galvanized iron pipe for corner on double proportion distance from the corner to Sections 10, 11, 14 and 15 to the west and the range corner to Sections 12 and 13 to the east, also corner to Sections 1, 2, 11 and 12 to the north and  $\frac{1}{4}$  corner to Sections 13 and 14 to the south.

- A 36" white oak scribed C.S.-BT bears N.19°W., 304.8 feet.
- Scribed a 34" white oak C.S.-BT which bears N.55°E., 147.2 feet.
- Set a 3 $\frac{3}{4}$ " x 30" iron pin which bears S.0°11'W., 40.0 feet. (3/4 in. diam. iron pin SMB 11/2019).
- Scribed a 14" white oak C.S.-BT which bears S.46 $\frac{1}{2}$ °W., 101.3 feet.

December 2, 1944  
C. Z. Boyden  
B. L. Campbell  
R. E. Welch

SEE NEXT PAGE FOR FIRST RE-ESTABLISHMENT

## FIRST RE-ESTABLISHMENT

GCDB 600500

Section corner common to Section 11, 12, 13, and 14 Twp. 35 South, Range 2 West, W.M.

Found, the 2 ins. diam. G.I. pipe in concrete as set by the County Public Works Dept., inside a monument case which is flush with the new surface of Beagle Road. This corner position was established by double proportion by the County Surveyor in 1944.

The  $\frac{3}{4}$  ins. iron pin set as a reference in 1944 brs. Record:  $S00^{\circ}11'W$ , 40.00 feet. Using this as a back sight, angles were turned by instrument to the following references:

- 20 ins. diam. white oak with two healed blazes brs.  $S46^{\circ}37'W$ , 101.6 feet to center of tree. Record:  $S46^{\circ}30'W$ , 101.3 feet.
- 40 ins. diam. white oak with two healed blazes brs.  $N18^{\circ}52'W$ , 306.4 feet to center of tree at lower blaze. Record:  $N19^{\circ}W$ , 304.8 feet.
- 34 ins. diam. white oak with partially chopped open blazes brs.  $N55^{\circ}12'E$ , 148.9 feet to center of tree at lower blaze. Record:  $N55^{\circ}E$ , 147.2 feet.
- $\frac{5}{8}$  ins. diam. iron pin set in Survey NO. 6336 brs.  $N45^{\circ}23'E$ , 56.57 feet.
- $\frac{3}{4}$  ins. G.I. pipe brs.  $S00^{\circ}02'45"E$ , 40.00 feet. This pipe is believed to be from Survey No. 1948.

July 28, 1977  
R. Roberts  
E. Graham

Approved by: Edward McGinty  
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SPECIAL CORNER

SECOND RE-ESTABLISHMENT

GCDB 600500

Corner common to Sections 11, 12, 13 and 14, Township 35 South, Range 2 West, W.M.

Found in monument case, the 2 ins. diam. iron pipe reported set on first re-establishment\*, page 9, in 1944. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T35S R2W	
11	12
-----	
14	13
CS	
1988	

Bearing trees recorded on said first re-establishment\* found and measured to center of trees at lower blaze:

- White Oak, now 36 ins. diam. with partially healed and rotted blazes, brs. Record: N55°E, 148.70 feet. Record distance; 147.2 feet.
- White Oak, now 20 ins. diam. with double healed blazes, brs. Record: S46½°W, 101.85 feet. Record distance; 101.3 feet.
- White Oak, now 42 ins. diam. with double healed blazes, brs. Record: N19°W, 305.78 feet. Record distance; 304.8 feet.

Reference set on said first re-establishment\* found:

- ¾ ins. diam. iron pin, found 4 ins. deep, brs. S½°W, 40.02 feet. Record: South, 40.00 feet.
- A ½ ins. diam. iron pipe is found 0.28 feet East of this pin.

Corner lies at the center line intersection of Beagle and Shiloh Roads.

April 27, 1988  
D. Edwards, Tech.  
T. Newcomb, Tech.

Edward McGinty  
County Surveyor

V = 17¾°  
P. - 177

\*NOTE: First re-establishment refers to establishment of Proportioned Corner in 1944. (05/11/2016)

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

**SPECIAL CORNER**

**THIRD RE-ESTABLISHMENT**

**GCDB 600500**

Section corner common to Sections 11, 12, 13 and 14, Township 35 South, Range 2 West, W.M.

Two and a half (2½) ins. diam. brass cap set in top of a 2 ins. diam. iron pipe on SECOND Re-establishment in 1988 is now missing. Set in top of said 2 ins. diam. iron pipe a 2½ ins. diam. brass cap, flush with asphalt and marked:

JACKSON COUNTY SURVEYOR  
T35S R2W  
S11 | S12  
—+—  
S14 | S13  
2005

Bearing trees and references recorded on Second Re-establishment in 1988, found in good condition and undisturbed. No measurements taken. See said Second Re-establishment for measurements.

Corner lies in a monument case at the centerline intersection of Beagle and Shiloh Roads.

January 18, 2005  
H. Durkee  
T. Newcomb

Roger R. Roberts  
Jackson County Surveyor

P.- 4


**SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT**

## FOURTH RE-ESTABLISHMENT

GCDB 600500

Section corner common to Sections 11, 12, 13, and 14, Township 35 South, Range 2 West, W.M.

Found the 2½ ins. diameter brass cap set on the Third Re-Establishment, dated 2005, now 1 ins. deep in asphalt, cap marked:



References found or set per Second Re-Establishment, dated 1988, found:

- ¾ ins. diam. rebar, found 2 ins. deep, brs. S 00°12'51"E 39.98 feet. Record S ½°W, 40.02 feet.
- A ½ ins. diam. open topped pipe brs. S 00°36'16"E 39.94 feet. Record S 00°02'45"E, 40.00 feet per First Re-establishment dated 1977.
- A now 22 ins. diameter white oak with double healed blazes brs. S 46°15'31"W 101.85 feet. Record: S 46°30'00"W

New References; 5/8 ins. diameter by 24 ins. long rebar with 2 ins. diameter aluminum cap marked "Jackson County Surveyor":

- Flush, brs. N 60°14'01" E 78.02 feet, point falls at Northeast corner of Beagle Rd. and Shiloh Rd. intersection and is +/- 25 feet Northerly of mail boxes
- Flush, brs. N 68°43'34" W 94.72 feet, point falls at the Northwest corner of Beagle Rd. and Shiloh Rd. intersection and is +/- 13 feet Northerly of the Northerly ditch top of bank and +/- 50 feet Westerly of a North and West bearing fence corner
- Flush, brs. S 70°51'55" W 110.84 feet, point falls at the Southwest corner of Beagle Rd. and Shiloh Rd. intersection and is +/- 18 feet Southerly of the Southerly top of bank and also +/- 5 feet Westerly of an East, West and South bearing fence corner

The First Re-establishment, dated 1980, brass capped quarter corner to said section 12, bears N 00°03'14" W 2642.63 feet.

Corner lies at the centerline intersection of Beagle Rd. and Shiloh Rd.

Basis of Bearing: NAD 83 2011 Epoch (2010) OCRS GP/ASH zone per OAR 734-005-0015

September 24, 2019  
J. Hall  
O. Ribanszky

Scott D. Fein  
Jackson County Surveyor