

FIRST RE-ESTABLISHMENT

GCDB 600600

Corner to Sections 1, 2, 11 and 12. Township 35 South, Range 2 West.

Found the original BT to southwest with scribe legible.

From which evidence set a 2" x 36" galvanized iron pipe 8" below the surface of the ground for corner.

- Scribed a 7" ash C.S.-BT which bears N.74°E., 392.5 feet.
- Scribed an 8" ash C.S.-BT which bears S.75¼°E., 479.2 feet.
- Scribed a 20" black oak C.S.-BT which bears S.51½°W., 396.9 feet.
- Scribed a 24" black oak C.S.-BT which bears N.69¾°W., 401.3 feet.
- Set a 5/8" x 24" iron pin which bears West 40.0 feet.

C. Z. Boyden
B. L. Campbell
R. E. Welch
December 6, 1944.

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 600600

Section corner common to Sections 1, 2, 11, 12, Township 35 South, Range 2 West, W.M.

Found, 8 ins. deep, the 2 ins. diam. iron pipe set on first re-establishment, page 8, in 1944.
Inside found pipe I set a 1x36 ins. G.I. pipe, 2 ins. below the surface of the ground (in concrete)
with a 2½ ins. bronze disc marked:

JACKSON COUNTY 1979
T35S R2W
2 | 1
—|—
11 | 12

The single original bearing tree recorded by Ives and Hyde in 1854, a White Oak, now 30 ins. diam., with axed and/or rotted out faces brs. S64°45'W, 324.87 feet to center of tree. Record: S64¾°W, 324.72 feet.

Reference trees recorded on first re-establishment found as follows:

- The most westerly branch 13 ins. diam. of a multiple (5) ash, with partially healed blazes, brs. N74°04'37"E, 392.47 feet to center of tree. Record: N74°E, 392.5 feet.
- Ash, 12 ins. diam., with healed blazes, brs. S75°13'15"E, 479.93 feet to center of tree. Record: S75¼°E, 479.2 feet
- Black Oak, 32 ins. diam. with healed blazes, brs. S51°27'22"W, 397.87 feet to center of tree. Record: S51¼ W, 396.9 feet
- White Oak, 29 ins. diam., with healed blazes, brs. N69°33'05"W, 402.43 feet to center of tree. Recorded as Black Oak, N69¾°W, 401.3 feet.
- The 5/8 ins. diam. iron pin found flush, noted on first re-establishment, brs. N89°30'25"W, 40.30 feet. Record: West, 40.0 feet.
- A found 3/4 ins. diam. iron pin at the corner of North-South and West brg. fence lines brs. N4°54'57"W, 32.60 feet

Corner lies about 32 feet S5°E from location marker on post fence corner and approximately 30 feet West of the center of Shiloh Road.

June 5, 1979
J. Swanson
R. Frost

Approved by: Edward McGinty
County Surveyor


SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 600600

Section corner common to Sections 1, 2, 11, 12, Township 35 South, Range 2 West, W.M.

Found the 2½ ins. diam. brass cap per Second Re-Establishment, dated 1979, loosely set and apparently disturbed leaning Southeasterly in concrete. Removed found monument and set a 2 in. x 60 ins. long galvanized iron pipe flush with ground with 2½ ins. diam. brass cap cemented in top. Cap marked;



References recorded on the Second Re-Establishment found;

- 5/8 ins. diam. smooth pin flush with ground, brs. N 89°35'00" W, 40.48 feet, Record N 89°30'25" W, 40.30 feet. Point falls +/- 33 feet westerly of North-South fence line and +/- 30 feet Southerly of an East-West fence line
- ¾ ins. diam. smooth pin exposed 3 ins. and leaning Southerly (measured to top of monument) brs. N 05°36'41" W, 32.61 feet. Record N 04°54'57" W, 32.60 feet. Point falls 0.5 feet Easterly of a North-South-West fence intersection
- Ash 17 ins. diam. the most westerly branch of 5 with double healed blazes, brs. N 73°41'42" E, 392.47 feet to center of tree at base. Record: N 74°04'37" E
- Rotted oak stump 36 ins. diam. brs. S 51°07'46" W, 397.87 feet to center of stump. Record S 51°27'22" W
- White Oak 31 ins. diam. with double healed blazes, brs. N 69°56'11" W, 402.43 feet to center of tree at base. Record N 69°33'05" W
- Note Ash bearing tree in the Southeast quadrant is now gone

Set New References; 5/8 x 24 ins. rebar with 2 ins. diam. aluminum caps marked "Jackson County Surveyor"

- 2 ins. deep, brs. N 65°21'50" E, 81.58 feet. Point falls +/- 2 feet Westerly of a North-South-East fence intersection
- 2 ins. deep, brs. S 41°34'38" E, 93.86 feet. Point falls on the Easterly side of Shiloh Road and is +/- 25 feet Easterly of a 1 mile marker post

Take new references as follows;

- Found yellow plastic cap marked "Bradshaw LS 2271" brs. N 89°35'06" E, 72.11 feet (Record: 72.01 feet per SN 20322). Point falls 0.5 feet westerly of a North-South barb wire fence and +/- 30 feet Southerly of a North-South-East fence intersection

The First Re-establishment, dated 1980, brass capped quarter corner to said section 12, bears S 00°03'06" E 2642.93 feet.

Corner falls +/- 25 feet westerly of an estimated centerline of Shiloh Road and +/- 30 feet Southerly of a North-South-West fence intersection

Basis of bearing: NAD 83 2011 Epoch (2010) OCRS GP/ASH zone per OAR 734-005-0015

October 9, 2019

J. Hall

O. Ribanszky

Scott D. Fein

Jackson County Surveyor