

PROPORTIONED CORNER – NO FIRST RE-ESTABLISHMENT

GCDB 600640

Quarter Corner to Sections 1 and 2, Township 35 South, Range 2 West, W.M.

No definite evidence of the original corner.

Set a 1" x 36" galvanized iron pipe 2" below the surface of the ground for corner on single proportion from the section corner to the north and south,

From which;

- A 14" white oak scribed C.S.-BT bears S.73½°W., 221.0 feet.
- Scribed an 8" white oak C.S.-BT which bears N.70°W., 332.3 feet.
- Set a ¾" x 30" iron pin S.78°38'W., 73.7 feet.
- Set a ¾" x 30" iron pin which bears N.78°38' E., 6.3 feet.

Note: No trees east of line.

December 7, 1944
C. Z. Boyden
B. L. Campbell
R. E. Welch

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SPECIAL CORNER

SECOND RE-ESTABLISHMENT

GCDB 600640

Quarter corner common to Sections 1 and 2, Township 35 south, Range 2 West, W.M.

Found flush, the 1 ins. diam. iron pipe reported set by proportionate measure on first re-establishment*, page 7, in 1944. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T35S R2W
¼S
2 | 1
CS
1988

References recorded on said first re-establishment* found:

- ¾ ins. diam. iron pin, found 1 ins. deep, brs. N71½°E, 6.25 feet. Record: N78°38'E, 6.3 feet.
- ¾ ins. diam. iron pin, found 2 ins. deep, brs. S71°W, 73.62 feet. Record: S78°38'W, 73.7 feet.
- White Oak, now 21 ins. diam. with double healed blazes, brs. Record: S73½°W, 221.35 feet to center of tree at lower blaze. Record distance; 221.0 feet.
- White Oak, the East fork and now 11 ins. diam. with double healed blazes, brs. Record: N70°W, 332.6 feet to center of tree at lower blaze. Record distance; 332.3 feet

Corner lies 1.2 feet Southwesterly from a corner post to fences bearing North and S16°E and 40 feet East of the middle of Shiloh Road.

April 27, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 18°
P.-172

*NOTE: First re-establishment refers to establishment of Proportioned Corner in 1944. (5/11/2016)