

## FIRST RE-ESTABLISHMENT

GCDB 700100

Township corner, Township 35 South, Range 1 and 2 West, and Township 36 South, Range 1 West, and 2 West, W.M.

This corner verified by check measurements to corners West, East, and South.

Set stone 5 x 5 x 24 inches with cross and raised mound of rocks 3 feet square.

From said corner:

- Power pole #236 bears N.72°20'E., 287.9 feet.
- Power pole #234 bears S.30°13'E., 271.2 feet.
- Poles scribed W.C. for witness corner.

A. T. Brown, Deputy County Surveyor  
H. Speck & H. Berrian, Chainmen  
September 4, 1914.

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 700100

Township corner - Township 35 South, Range 1 and 2 West and Township 36 South, Range 1 and 2 West, W.M.

Found a 2" x 4" x 16" sandstone with lead center point for corner; also found the two power poles lying on the ground with W.C. scribes visible, which poles have recently been removed. However, the holes where the poles were located are in evidence, which holes check with the re-establishment record by County Surveyor Brown dated September 4, 1914.

From the said sandstone with lead center point for corner:

- An 8" White Oak scribed C.S.-BT bears S64°E, 367.9 feet.
- A new power pole bears S52°E, 225.7 feet.
- Scribe an 8" White Oak C.S.-BT which bears S9°W, 563.5 feet.
- Scribe a 12" White Oak C.S.-BT which bears N48°E, 599.5 feet.
- Set a ¾" x 19" iron bolt 19" in the ground which bear West 85.0 feet.

March 13, 1941  
C. Z. Boyden  
C. I. Bourne  
A.H. Smith  
April 1942

### NOTE:

The sandstone with lead center has been replaced with a 6"x6"x? concrete monument with 2" brass disk.

C. Z. Boyden  
April 1942

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

### THIRD RE-ESTABLISHMENT

GCDB 700100

Township corner - Township 35 South, Range 1 and 2 West and Township 36 South, Range 1 and 2 West, W.M.

Found a 2 ins. diam. brass cap marked:

T35S	
S36	S31
—	
S1	S6
R2W R1W	
T36S	
1941	

Set in a 6 x 6 x ? concrete monument (U.S. Army). This monument replaced the stone set by A. T. Brown in 1914.

Take the following references: Found  $\frac{5}{8}$  ins. diam. rebars with yellow plastic caps marked "Kaiser RLS 808" protruding 4 ins. above ground surface, set on recorded survey #10129 dated 1984.

- S89°54'15"E, 137.51 feet.
- S00°06'25"W, 323.83 feet.

Set  $\frac{5}{8}$  ins. diam. rebar, with yellow plastic cap marked "Jackson C.S." protruding 4 ins. above ground surface on a projected line South of a North South bearing fence line at an angle point in said fence line and 2 feet South of 16 ins. diam. anchor post, brs. N00°08'45"E, 375.94 feet.

The southerly end peak of a tin roofed barn brs. N81°36'15"W, an estimated  $\frac{1}{2}$  mile. (see field notes)

Corner lies on an East-West fence line in a swampy pasture and 177 feet West of the center line of Modoc Rd.

August 6, 1990  
S. Beecher, Tech.  
T. Newcomb, Tech.

Verlyn Thomas  
County Surveyor

P.-122