

FIRST RE-ESTABLISHMENT

GCDB 700200

Section corner common to Sections 25, 30, 31, and 36, Township 35 South, Range 1 and 2 West,
WM $V = 20\frac{1}{2}^\circ$

Set a 1 x 36 ins. G.I. pipe with brass cap 27 ins. deep $2\frac{1}{2}$ feet West of a North-South fence. Bronze cap stamped:

T35S
R2W R1W
S25 | S30
—+—
S36 | S31
1974
Jackson County

From which the following evidence was located by transit and tape:

- Original 12 ins. White Oak, now 15 ins. hollow tree with reverse scribe marks, bears $N34^\circ47'E$, 37.94 feet to center of tree. Record, $N35\frac{1}{2}^\circ E$, 38.28 feet.
- Original 13 ins. White Oak, now a 15 ins. tree with rotted face, bears $N11^\circ05'W$, 45.67 feet to center. Record, $N11^\circ05'W$, 45.54 feet.
- Original 8 ins. White Oak, now 13 ins. tree with recent new scribe in upper face and original lvs and Hyde "B" in newly opened lower blaze, bears $S73^\circ42'E$, 62.88 feet to center. Record, $S72\frac{1}{2}^\circ E$, 61.38 feet.
- Original 6 ins. White Oak, now a 10 ins. tree with scribed BT, bears $S12^\circ27'W$, 52.83 feet to center. Record, $S12\frac{1}{2}^\circ W$, 52.80 feet.
- A found $\frac{3}{4}$ ins. pipe bears $S80^\circ21'E$, 3.58 feet. Reference: Survey #3624.

New trees marked C.S. BT and measurements taken to center of trees at lower blaze:

- A White Oak, 6 ins. diam., bears $N39\frac{1}{2}^\circ W$, 30.45 feet.
- A White Oak, 10 ins. diam., bears $N20\frac{1}{2}^\circ E$, 102.70 feet.
- A White Oak, $7\frac{1}{2}$ ins. diam., bears $S32^\circ E$, 61.12 feet.
- A White Oak, $9\frac{1}{2}$ ins. diam., bears $S35\frac{1}{4}^\circ W$, 53.64 feet.

March 26, 1974

E. Graham

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor