

## FIRST RE-ESTABLISHMENT

GCDB 700240

Quarter corner common to Section 25, Township 35 South, Range 2 West, and Section 30, Township 35 South, Range 1 West, WM  $V = 20\frac{1}{2}^\circ$

Found  $\frac{5}{8}$  ins. re-bar for corner point from which a Y. Pine, 27 ins. diam., with healed blazes, bears record,  $S13^\circ W$ , 59.7 feet.

A White Oak,  $17\frac{1}{2}$  ins. diam., now hollow with reverse scribe visible from back side, bears record:  $N63^\circ E$ , 45.2 feet.

Measured to center of trees, replaced said  $\frac{5}{8}$  ins. rod with a 1 ins. x 36 ins. G.I. pipe and a  $2\frac{1}{2}$  ins. bronze cap flush with ground and marked:

T35S  
R2W R1W  
 $\frac{1}{4}$  S25 | S30  
1974  
Jackson County

Buried found re-bar along east side as a memorial.

New trees marked C.S. BT and measurements taken to center of trees at lower blaze:

- A White Oak, 12 ins. diam., bears  $N8^\circ W$ , 77.60 feet.
- A White Oak, 11 ins. diam., bears  $S47\frac{1}{2}^\circ E$ , 75.05 feet.
- N-S-W fence lies Westerly 10 feet.

March 26, 1974  
Ed Graham  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor