

FIRST RE-ESTABLISHMENT

GCDB 700300

Corner on range line Section 19 and 30, Township 35 South, Range 1 West, Section 24 and 25, Township 35 South, Range 2 West, W.M.

Found all four BTs. BT to Southwest fallen down.

Set a 3/8" x 8" bolt in county road for corner from which;

- The original BT, A 20" yellow pine bears N.79°30'E., 31.7 feet.
- A 12" white oak, the original BT, bears N.39°W., 75.2 feet.
- A 24" yellow pine, the original BT, bears S.23°30'E., 25.0 feet
- Scribe an 8" white oak C.S.-BT which bears S.45°30'W., 71.4 feet.

September 21, 1929
C. Z. Boyden, Deputy County Surveyor
Tice and E. H. Judd, Chainmen
Tice and C. Bourne, Chainman

NOTE: November 6, 1929

Replaced bolt with a stone 12x10x8," 8" below the surface of the ground.

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 700300

Section Corner on Range Line - Sections 24 & 25, T. 35 S., R. 2 W. & Sections 19 & 30, T. 35 S., R. 1 W.

Found original BT, a 14" white oak, which bears N.39°W., 75.2 feet; also re-established BT, a 10" white oak, which bears S.45½°W., 71.4 feet. BT to southeast dead. BT to northeast cut down. No evidence of stone for corner.

Set a ¾" x 17" iron pipe with top 2" below surface of the ground for corner and scribed the following BTs:

- A 10" white oak scribed C.S.-BT bears N.20¼°E., 64.8 feet.
- A 14" white oak scribed C.S.-BT bears S.11¾°E., 45.4 feet.

September 25, 1944
C. Z. Boyden
B. L. Campbell
L. J. Shorey

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 700300

Section corner common to Sections 24 and 25, Township 35 South, Range 2 West and Sections 19 and 30, Township 35 South, Range 1 West, W.M.

At the corner, found 6 ins. deep, the 3/4 ins. diam. iron pipe set on second re-establishment page 14 in 1944.

In the top of said pipe, set a 2 1/2 ins. diam. brass cap mkd:

T35S	
R2W	R1W
24	19

25	30
C.S.	
1983	

From which:

- An original bearing tree recorded by Ives and Hyde in 1854, a White Oak, now 19 ins. diam., with healed blazes, brs. N39°08'W, 75.5 feet to center. Record: N38 1/2°W, 75.24 feet.
- A White Oak, marked on first re-establishment, page 4, in 1929, now 16 ins. diam. with healed blazes, brs. S45°50'W, 72.00 feet to center. Record: S45°30'W, 71.4 feet.

Bearing trees marked on second re-establishment found:

- White Oak, 19 ins. diam. (at lower blaze) with healed blazes, brs. N20°06'E, 65.33 feet to center of tree. Record: N20 1/4E, 64.8 feet
- The center of White Oak stump remains brs. S11°13'E, 45.8 feet Record: S11 3/4°E, 45.4 feet.

Marked a new tree "CS" "BT":

- White Oak, 12 ins. diam., brs. S31°27'E, 83.6 feet.

Corner lies on projected North-South fence line in the middle of Glass Lane.

E. McGinty
R. Frost
September 8, 1983

Edward McGinty
County Surveyor


P.-95

SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT

**FOURTH RE-ESTABLISHMENT
GCDB 700300**

Section corner common to Sections 24 and 25, Township 35 South, Range 2 West and Sections 19 and 30, Township 35 South, Range 1 West, W.M.

At the corner, fd. 6 ins. deep, the 22 ins. diam. brass cap set on the Third Re-establishment, dated 1983, mkd:



Cap has been hit several times by digging bars.

Found the following references:

Original bearing tree marked by Ives and Hyde in 1854;

- White Oak 23 ins. diam. with healed blazes, bears 1983 record, N39°08'W, 75.5 ft. to center of tree at base.
- Second Re-establishment, dated 1944; Dead White Oak 21 ins. diam., bears N20°06'E, 65.3 ft. to center of tree at base. 1983 record 65.33 ft.
- Third re-establishment; White oak 14 ins. diam. with healed blazes, bears record S31°27'E, 83.6 ft. to center of tree at base.

Set new references as follows;

- Mag nail 1.7 ft. high in the West side of easterly 8 ins. diam. post to 'BAR J' sign, bears N10°21'W, 48.32 ft. Sign located at 544 Glass Lane.
- Mag nail in southerly edge at top of 9 ins. diam. x 4 ft. high concrete filled post bears S80°05'W, 81.74 ft. Post is located at southerly end of gate at the West end of traveled way of Glass Lane.

Corner is located near the visual center line of Glass Lane, approx. 80 ft. East of the terminus of traveled way.

November 10, 2011
S. Beecher
S. Fein

Kerry K. Bradshaw
County Surveyor

P.-16
Series II Book I