

FIRST RE-ESTABLISHMENT

GCDB 700400

Section corner on range line between Sections 13 and 24, Township 35 South, Range 2 West and Sections 18 and 19, Township 35 South, Range 1 West.

Found original BT to NE from which set a 2" x 36" galvanized iron pipe 33" in the ground for corner from which the original BT a 14" white oak bears N.18°E. 471.3 feet.

Scribe a 16" white oak CS-BT which bears N.2°10' W. 555.0 feet.

August 23, 1930
C. Z. Boyden
L. Pettegrew
Dave King

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 700400

Section corner on range line between Sections 13 and 24, Township 35 South, Range 2 West and Sections 18 and 19, Township 35 South, Range 1 West.

Found the galvanized 2" iron pipe corner monument with top 4" above the ground surface, set on first re-establishment by Deputy County Surveyor, C. Z. Boyden on August 23, 1930.

Found original bearing tree to the Northeast down and badly rotted.

Found the re-established bearing tree with blazes healed (now a 20" White Oak) which bears North $1^{\circ} 58'$ West, 554.9 feet to the face of the upper blaze.

From said pipe corner, I establish a new witness tree:

- A 12" White Oak scribed "CS-BT" bears North $72^{\circ} 05'$ East, 499.9 feet to the face of the lower blaze.

June 17, 1966

F. Roberts

G. Nygren

Approved By:

Mark E. Boyden, County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 700400

Section corner common to Sections 18 and 19, Township 35 South, Range 1 West, and Sections 13 and 24, Township 35 South, Range 2 West, W.M.

At the corner, found 2 ins. diam., galvanized iron pipe projecting 2 ins. recorded on second re-establishment, in 1966. Set in concrete in the top of said pipe, brass cap marked:

T35S	
R2W	R1W
13	18
— —	
24	19
C.S.	
1981	

Bearing trees recorded on above noted re-establishment found:

- The most westerly branch, 14 ins. diam., with healed blazes, of a double White Oak brs. N71°57'E, 499.99 feet to center of said branch at lower blaze. Record: N72°05'E, 499.99 feet to face of lower blaze.
- White Oak, 19 ins. diam., with healed blazes, brs. N2°06'W, 555.63 feet to center of tree at lower blaze. Record: N1°58'W, 554.9 feet to face of upper blaze.

Set new references; rebars, 5/8 ins. diam., 30 ins. long, flush with the ground with yellow plastic caps marked "JACKSON C.S." brs.:

- S89°00'W, 49.91 feet located on E-W fence line.
- N0°26'W, 49.85 feet located on N-S fence line.

Corner lies about 2.5 feet S60°E of the wood post corner of N-W bearing fence line.

March 23, 1981
R. Frost
R. Templin

Edward McGinty
County Surveyor

P. -51