

FIRST RE-ESTABLISHMENT

GCDB 700500

Section corner common to Sections 7 and 18, Township 35 South, Range 1 West, and Sections 12 and 13, Township 35 South, Range 2 West, W.M.

- Found stone set for corner from which the original BT, a black oak checks perfectly.
- Set a 2 x 36" galvanized pipe 20" in the ground for corner from which;
- An 8" white oak scribed C.S.-BT bears N.74°30'E., 301.0 feet.
- A 22" black oak scribed C.S.-BT bears S.55°30'E., 346.0 feet.

December 3, 1929
C. Z. Boyden, Deputy County Surveyor
O. H. Tice, C. Bourne, Chainmen

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 700500

Section Corner on Range Line - Sections 12 and 13, Township 35 South, Range 2 West and Sections 7 and 18, Township 35 South, Range 1 West.

Found 2" x 36" galvanized iron pipe set for corner; also re-established BT to northeast.

- Scribed a 12" white oak C.S.-BT which bears N.40½°E., 302.4 feet.
- Scribed a 14" white oak C.S.-BT which bears S.78¼ E., 468.2 feet.
- Set a 5/8" x 30" iron pin which bears N.45°E., 56.57 feet.
- Set a 5/8" x 24" iron pin which bears N.45°W., 56.57 feet.

December 2, 1944

C. Z. Boyden

B.L. Campbell

R.E. Welch

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 700500

Section corner common to Sections 7 and 18, Township 35 South, Range 1 West, and Sections 12 and 13, Township 35 South, Range 2 West, W.M.

At the corner, found the 2 ins. diam. galvanized iron pipe, projecting 5 ins., recorded on second re-establishment, dated 1944.

Set in concrete in the top of said pipe, brass cap marked:

T35S	
R2W	R1W
12	7

13	18
C.S.	
1981	

From which references recorded on above noted re-establishment found as follows:

- White Oak, 20 ins. diam. with healed blazes, brs. S78°06'E, 468.34 feet to center of tree at lower blaze. Record: S78¼°E, 468.2 feet.
- Smooth iron pin, 5/8 ins. diam., located 1 feet North of east-west fence brs. N45°23'W, 56.41 feet.

Bearing tree recorded on first re-establishment, in 1929,

- White Oak, now 12 ins. diam. with healed blazes, brs. N74°36'E, 301.23 feet to center of tree at lower blaze. Record N74°30'E, 301.0 feet.

An original bearing tree recorded by Ives & Hyde in 1854,

- A Black Oak, now 22 ins. diam., with axed and/or rotted out faces, brs. N83°58'E, 348.62 feet to center of tree. Record: N84°E, 348.48 feet.

A found iron pin, 5/8 ins. diam. with yellow plastic cap marked "Moffit PLS 944" found flush, brs. N0°09'E, 25.00 feet.

Set a new reference:

- Re-bar 5/8 ins. diam. 30 in. long, flush, with yellow plastic cap marked "JACKSON C.S.", located 2 feet South of power pole No. 3800, brs. S45°22'E, 55.79 feet.

Corner lies at P.I. of Beagle Road.

March 23, 1981
R. Frost
R. Templin

Edward McGinty
County Surveyor

P.-50