

## FIRST RE-ESTABLISHMENT

GCDB 700640

Quarter corner common to Section 1, Range 2 West and Section 6, Range 1 West, Township 35 South, W.M.

Found at the corner position, exposed 4 ins. and in a small mound of stones,  $\frac{5}{8}$  x 24 ins. smooth galvanized iron pin set by Edward McGinty on Job No. 69-14 in 1969. Bob Malotte was present.

Set over top of said pin, 1 x 30 ins. flanged galvanized iron pipe 22 ins. deep with a 2½ ins. diam. brass cap marked:

JACKSON COUNTY SURVEYOR

T35S

¼

S1 • S6

R2W R1W

2002

Original evidence recorded by Ives and Hyde in 1854 found:

- Root hole with burnt pine remains brs. record N12°W, 17.16 feet (no other pine trees in immediate area).
- Clump of young White Oaks brs. record S31°E, 32.34 feet.

Mark new bearing trees "CS" "BT" and take measurements to center of tree at lower blaze:

- White Oak 7 ins. diam. brs. N24°W, 99.0 feet.
- White Oak 6 ins. diam. brs. N71°E, 15.3 feet.
- White Oak 5 ins. diam. brs. S50°E, 11.45 feet.
- Manzanita 4 ins. diam. brs. S5°W, 29.20 feet.

Found ½ in. diam. rebars exposed 6 ins. which br.:

- N24°W, 96.35 feet.
- N½°E, 34.0 feet.

Search Coordinates:    42°33.3889'  
                                 122°52.5602'

Corner lies on westerly slope approximately 40 feet east of gulch. C. - south

November 6, 2002

H. Durkee

T. Newcomb

Roger R. Roberts

Jackson County Surveyor

P. - 212

V. - 19°