

FIRST RE-ESTABLISHMENT

GCDB 100200

Section corner to Section 30 and 31, Township 36 South, Range 1 East, and Section 25 and 36, Township 36 South, Range 1 West, W.M.

Found original BT to SW intact; also tree and stump of BT to NE which has been cut down. Scribe visible in both B.T`s.

Set 2" x 36" galvanized pipe for corner at intersection of distance from BTs which checks course to BT to SW.

Course to BT to NE 20° off, being N84°E., and original notes call for N64°E, also find sprouts of Oak at the location for original BT to NW, from pipe set for corner.

Scribe a 8" forked White Oak C.S.-BT, which bears S48°30'E, 80.4 feet.

- A 16" White scribed C.S.-BT, which bears S48°30'E, 80.4 feet.
- A 16" White scribed C.S.-BT, bears N51°45'E, 99.6 feet.

The centerline of irrigation canal bears North 52.0 feet. The centerline of high tension line bears West 15.0 feet.

June 29, 1928
Boyden, Deputy County Surveyor
O. Tice, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 100200

Corner common to Sections 25 and 36, Township 36 South, Range 1 West and Sections 30 and 31 Township 36 South, Range 1 East, W.M.

Found a 6"x6" concrete monument exposed 6" with a 2" bronze disk stamped:

T. 36 S.	
S 25	S 30
— —	
S 36	S 31
R1W	R1E
1941	

For corner from which:

- The original bearing tree (now a 19" White Oak with the lower face open and rotted out) bears $S28^{\circ}W$, 112.3 feet to the face of the lower blaze (original Record: 16" White Oak $S28^{\circ}W$, 112.2 feet).
- The original White Oak bearing tree to the Southeast (referred to as Northeast in the First re-establishment by Deputy County Surveyor C. Z. Boyden on June 29, 1928) now a stump hole with Oak remains, bears $S84^{\circ}E$, 12.9 feet to the center (original Record: 9" White Oak $S64^{\circ}E$, 12.5 feet: First re-establishment: sawed stump $N 84^{\circ}E$).
- The bearing tree established on the said first re-establishment, (now an 8" twin White Oak with healed faces) bears $S48\frac{1}{4}^{\circ}E$, 80.6 feet to the center of the Southwesterly twin;
- The bearing tree established on said first re-establishment (now a 14" White Oak with open faces and scribe visible) bears $N51\frac{3}{4}^{\circ}E$, 99.6 feet to the face of the upper blaze.
- The centerline of a power transmission line bears West, 15 feet.

Establish new references as follows:

- A 9" White Oak scribed "CS-BT" bears $N78\frac{1}{2}^{\circ}W$, 95.9 feet to the face of the lower blaze.

January 21, 1971
Gary Kaiser, Deputy County Surveyor
Lloyd Shreeve