

GCDB 100340

Quarter Corner on Willamette Meridian, Section 24, Township 36 South, Range 1 West, and Section 19, Township 36 South, Range 1 East, W.M.

Set a 1" x 35" galvanized iron pipe 3" below the surface of the county road for corner, from which;

- A 16" White Oak scribed CS-BT bears $N27\frac{1}{2}^{\circ}E$, 313.6 feet.
- Scribed a 16" White Oak CS-BT which bears $S88\frac{3}{4}^{\circ}E$, 300.2 feet.

No trees near West of line.

April 6, 1945
C. Z. Boyden
R. E. Welch
F. Foley
L. J. Shorey

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 100340

Quarter corner common to Sections 24, Township 36 South, Range 1 West, and Section 19, Township 36 South, Range 1 East, W.M.

Found, 12 ins. below the asphalt surface of Meridian Road, the 1 ins. diam. iron pipe recorded as the corner on first re-establishment in 1945.

To perpetuate this position I set $\frac{3}{4}$ x 15 ins. rebar inside found pipe in concrete 2 ins. below road surface with $2\frac{1}{2}$ ins. diam. bronze disc marked:

JACKSON COUNTY 1980
T36S
24 | 19
R1W R1E
CS

From which bearing trees marked in 1945, found as follows:

- White Oak, dead, 18 ins. diam., with rotted faces partially exposed, brs. N27°30'E (basis of bearing) 314.04 feet to center of tree at upper face. Record N27½°E, 313.6 feet.
- White Oak, 32 ins. diam. with healed blazes, brs. S88°42'E, 301.25 feet to center of tree at lower blaze. Record; S88¾°E, 300.2 feet.

I set new references:

- $\frac{5}{8}$ x 30 ins. rebar, located 18 ins. Southeast of power pole B-13540 and 6 ins. East of fence line course; North-South, with yellow plastic cap marked "JACKSON C.S.", flush with the ground, brs. N39°38'E, 63.47 feet
- $\frac{5}{8}$ x 24 ins. rebar, located under approximate center of overhead transmission lines course North-South, about 2.5 feet South of corner of intersection of South and East-west fence lines and 5 feet Southwest of the corner of North and West bearing fence lines, with yellow plastic cap marked "JACKSON C.S." flush with the ground, brs. N25°04'W, 64.44 feet.

January 24, 1980
J. Swanson
R. Frost

Approved by: Edward McGinty
County Surveyor