

**PROPORTIONED CORNER – NO FIRST RE-ESTABLISHMENT**

**GCDB 100440**

Quarter Corner on Willamette Meridian, Section 13, Township 36 South, Range 1 West and Section 18, Township 36 South, Range 1 East, W.M.

Set a 1" x 30" galvanized iron pipe 28" in the ground for corner on single proportion distance,

From which;

- A 10" White Oak scribed CS-BT bears N71¼°W, 66.1 feet.
- Scribed an 8" White Oak CS-BT which bears S72½°W, 96.2 feet.

No trees near East of Line.

April 6, 1945  
C. Z. Boyden  
R. E. Welch  
F. Foley  
L. J. Shorey

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 100440

Quarter corner common to Sections 13, Township 36 South, Range 1 West, and Section 18, Township 36 South, Range 1 East, W.M.

Set a 1" x 36" galvanized iron pipe 40" in the ground with a 2½" bronze cap stamped:

T36S, R1W-1E  
1972  
¼ 13 | 18 Cor.  
C.S.

From which:

- Southwest bearing tree established on the First re-establishment\* by Deputy County Surveyor C. Z. Boyden on April 6, 1945, now a 12" White Oak with healed blazes, bears S72°28'W, 96.6 feet to the center (First re-establishment, 8" White Oak S72½°W, 96.2 feet.)
- The Northwest bearing tree established on said First re-establishment, now a 14" White Oak with upper face open and scribe visible, bears N71°10'W, 66.5 feet to the face of the upper blaze (First re-establishment, 10" White Oak, N71¼°W, 66.1 feet.)
- Said pipe corner monument is one foot West of west edge pavement.

December 28, 1972  
G. Kaiser, Deputy County Surveyor  
L. Shreeve

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

### THIRD RE-ESTABLISHMENT

GCDB 100440

Quarter corner common to section 13, Township 36 South, Range 1 West, and Section 18, Township 36 South, Range 1 East, W.M.

Found at the corner position and 1 in. deep, the 2½ ins. diam. brass cap set on Second Re-establishment in 1972, marked:

T36S R1W-1E  
1972  
¼ 13 • 18 COR.  
C.S.

Bearing trees recorded on First Re-establishment in 1945, found with double healed blazes and measured to center of trees at lower blaze:

- White Oak, now 15 ins. diam. brs. Record: S72½°W, 96.6 feet.
- White Oak, now 18 ins. diam. brs. Record: N71¼°W, 66.5 feet.

Take new references, 5/8 in. diam. rebar right-of-way monuments per Survey No. 6794, brs.:

- N 10°09'25" W, 90.43 feet (found flush and 0.1 feet west of the north-south fence line).
- N 26°20'18" E, 98.79 feet (found exposed 2 ins. and 0.4 feet west of north-south fence line).

Corner lies approximately 1 in. deep, 2 feet west of west edge of pavement and 900 feet north of Hwy. 140.

July 28, 2005  
H. Durkee

Roger R. Roberts  
Jackson County Surveyor

P. - 104


**SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT**

## FOURTH RE-ESTABLISHMENT

GCDB 100440

Quarter corner common to section 13, Township 36 South, Range 1 West, and Section 18, Township 36 South, Range 1 East, W.M.

Found at the corner position and 2 in. deep, the 2½ ins. diam. brass cap set on Second Re-establishment in 1972, marked:



Bearing tree recorded on First Re-establishment in 1945, found with double healed blazes and measured to center of trees at lower blaze:

- W. oak, 15 ins. diam. (in clump of oaks on fence line). brs. 1972 record; S72°28'W, 96.6 ft.

Third Re-establishment, dated 2005, references found, 5/8 in. diam. rebar right-of-way monuments per Survey No. 6794:

- Flush and located 0.1 ft. west of the north-south fence line bears N10°09'25"W, 90.45 ft. Record 90.43 ft.
- The northeasterly pin is found bent and is not measured.

Set new references 5/8 x 24 ins. rebar with 2 ins. diam. aluminum caps mkd.

JACKSON COUNTY  
△  
SURVEYOR

- Flush with gravel on the East shoulder of Meridian Rd. and 5 ft. East of pavement edge and 20 ft. northwest of power pole #B16412, brs. N89°08'42"E, 30.57 ft.
- Flush with gravel on the West shoulder of Meridian Rd. and 4 ft. West of pavement edge, brs. N02°36'44"W, 35.76 ft.

Corner is located approximately 2 in. deep, 2 ft. west of west edge of pavement and 900 ft. north of Hwy. 140.

May 1, 2012  
S. Beecher

Kerry K. Bradshaw  
County Surveyor

P. - 43