

FIRST RE-ESTABLISHMENT

GCDB 100640

Quarter corner common to Section 1, Township 36, Range 1 West and Section 6, Township 36 South, Range 1 East, W.M.

Found stake in mound of stone from which the original BT to NE checks O.K.

Set 1" x 36" galvanized pipe in mound of stone for corner

From which:

- Scribe 6" White Oak C.S.-BT, which bears N48°20'E, 83.7 feet. The centerline of high tension line bears West 35.3 feet.

June 29, 1928
Boyden, Deputy County Surveyor
O. Tice, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 100640

Quarter corner common to Section 1, Township 36 South, Range 1 West and Section 6, Township 36 South, Range 1 East, W.M.

Found a 6" x 6" x ? concrete monument exposed 2" with a 2" bronze disk stamped:

¼
S1 | S6
R1W | R1E
T36S
1941

From which:

- The center of the original bearing tree (now a 31" Black Oak stump) bears N31°20'E, 331.2 feet.
- Found no evidence of the corner monument or bearing tree established by Deputy County Surveyor C. Z. Boyden on June 29, 1928.
- The approximate center of a power transmission line bears West, 35.0 feet.

In April of 1945, C. Z. Boyden recognized said concrete monument as being the true corner location while establishing the Meridian Road center line control and for proportionate corners set Southerly from said monument on the Willamette Meridian.

From said concrete corner monument,

- Scribed a 7" White Oak, "CS-BT" which bears N36°33'E, 126.6 feet to the face of the lower blaze.
- Scribed a 12" White Oak, "CS-BT" which bears N21°35'W, 294.2 feet to the face of the lower blaze.

February 19, 1970
Otis Blankenship
Dan Phillips

Approved By: Mark E. Boyden
County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 100640

Quarter corner common to Section 1, Township 36 South, Range 1 West and Section 6, Township 36 South, Range 1 East, W.M.

Found a 6 x 6 ins. concrete monument projecting 2 ins., with a 2½ ins. diam. brass cap marked:

¼
S1 | S6
R1W R1E
T36S
1941

- Bearing tree marked on Second re-establishment, dated 1970 found
- NE bearing tree has been cut down a week back and the stump pulled up for clearing of a field by land owner.
- White Oak, 17 ins. diam., with healed blazes, brs. N21°36'W, 294.69 feet to the center of tree at lower blaze. Record; N21°35'W, 294.20 feet to lower face.

Used section corner to the South for back sight to determine bearing.

- Set a 5/8 x 24 ins. rebar with aluminum cap marked "Jackson County CS" set flush, brs. S63°22'E, 29.63 feet.
- Power Pole No. 394, brs. S16°24'30", 98.06 feet.
- Power Pole No. 4/49, brs. N77°25'20"W, 35.00 feet.

Corner lies on East edge of road and gateway.

October 9, 1992
T. Newcomb, Tech.
J. Burgess

Verlyn Thomas
County Surveyor

P.-107