

FIRST RE-ESTABLISHMENT

GCDB 140500

Quarter corner common to Sections 7 and 18, Township 36 South, Range 1 East, W.M.

Set a 1" x 36" galvanized iron pipe 46" in the ground with a 2½" bronze cap stamped:

T.36S. R. E.
7
¼S — Cor.
18
C.S.
1971

From which:

- The original bearing tree (now a 42" Black Oak with scribe visible) bears $S85\frac{3}{4}^{\circ}E$, 512.2 feet to the face of the upper blaze (Record = 6" Black Oak bears $S85\frac{3}{4}^{\circ}E$, 512.2 feet)
- The original bearing tree to the Northeast, now a triple 50" Black Oak, bears $N88\frac{1}{4}^{\circ}E$, 642.6 feet to the center of the clump (Record: 7" Black Oak bears $N88^{\circ}E$, 646.8 feet). This tree is not visible from the corner, as it falls on the opposite side of hill.
- Set a $\frac{3}{4}$ " x 36" galvanized iron pipe flush which bears $S85\frac{3}{4}^{\circ}E$, 268.9 feet;
- A 4" Pear tree bears $N72^{\circ}E$, 6.7 feet to the center;
- A 2" Pear tree bears $S19\frac{3}{4}^{\circ}E$, 19.0 feet to the center;
- A 3" Pear tree bears $S37\frac{1}{4}^{\circ}W$, 22.2 feet to the center;
- A 3" Pear tree bears $N82\frac{1}{4}^{\circ}W$, 13.2 feet to the center;
- An irrigation ditch, course South, bears East, 250 feet.

August 9, 1971
Gary Kaiser, Deputy County Surveyor
Dan Phillips