

FIRST RE-ESTABLISHMENT

GCDB 140600

Quarter corner common to Sections 6-7, Township 36 South, Range 1 East.

Found original BT to SE intact, from which set a 1" x 36" galvanized pipe for corner, from which

- The original BT a 30" black oak plainly scribed bears S81°E, 182.8 feet.
- A 12" black oak scribed C.S.-BT bears N78°15'E, 179.7 feet.

February 17, 1931
Boyden, Deputy County Surveyor
Tice & Pettegrew, Chainmen

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 140600

Quarter corner common to Sections 6 and 7, Township 36 South, Range 1 East, W.M.

Found projecting 5 ins., the 1 ins. diam. iron pipe reported set on first re-establishment, page 1, in 1931. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T36S R1E
6
¼S —
7
C.S.
1988

Original bearing tree marked by Ives and Hyde found:

- Black Oak snag, 36 ins. diam. with chopped and rotted face and supporting same live growth, brs. Record: S81°E, 183.85 feet to center of tree at root crown. Record distance; 182.8 feet to face.

Bearing tree marked on said first re-establishment found:

- Black Oak, now 17 ins. diam. with double healed blazes, brs. Record: N78¼°E, 182.5 feet to center of tree at lower blaze. Record distance; 179.7 feet to face.

Corner lies in a large opening, 33 feet North of a fence line bearing N85°W.

March 10, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 18½°

P. - 87