

FIRST RE-ESTABLISHMENT

GCDB 200200

Section corner common to sections 29, 30, 31 and 32, Township 36 South, Range 1 East, W.M.

Found original BT, a 24" Black Oak with scribe legible from which tree set a 2" x 36" galvanized iron pipe 34" in the ground for corner from which the above-described tree bears N28°E, 35.65 feet (Government Record):

- A 5" White Oak, scribed CS-BT bears N19½°W, 28.7 feet.
- A 10" White Oak, scribed CS-BT bears S81°W, 30.8 feet.
- A 10" Black Oak scribed CS-BT bears S31°E, 184.5 feet.

June 6, 1945
C. Z. Boyden
R.E. Welch
F. Foley

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 200200

Section corner common to Sections 29, 30, 31 and 32, Township 36 South, Range 1 East, W.M.

Found projecting 1 ins., the 2 ins. diam. iron pipe reported set on first re-establishment, page 9, in 1945. Inside of said pipe, set a 1 x 36 ins. galvanized iron pipe 26 ins. in the ground. In the top of new pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T36S R1E	
30	29

31	32
CS	
1988	

Original bearing tree marked by Ives and Hyde in 1854 found:

- Stump hole with axed remains lying alongside, brs. Record: N28°E, 36.2 feet to center of stump hole. Record distance; 35.65 feet.

Bearing trees marked on said first re-establishment found with double healed blazes and measured to center of trees at lower blaze:

- Black Oak, now 15 ins. diam., brs. S30°E, 183.6 feet. Record; S31°E, 184.5 feet.
- White Oak, now 14 ins. diam., brs. S82½°W, 30.35 feet. Record; S81°W, 30.8 feet.
- White Oak, now 9 ins. diam., brs. N17½°W, 29.08 feet. Record; N19½°W, 28.7 feet.

Mound stones around corner and scribe a new tree CS-BT:

- Black Oak, 13 ins. diam., brs. N28°E, 60.0 feet to center of tree at lower blaze.

Corner lies in Madrone and Oak openings, on an 18% West slope, 5.7 feet South of an East-West fence and an estimated 150 feet East of irrigation canal, course S4°W.

March 9, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 18½°
P. - 77