

FIRST RE-ESTABLISHMENT

GCDB 200400

Section corner common to Sections 17, 18, 19 and 20, Township 36 South, Range 1 East, W.M.
 $V = 20\frac{1}{4}^\circ$

In a found mound of stones I set a 1 x 36 ins. G.I. pipe 30 ins. in the ground with a 2½ ins. bronze disc marked:

T36S R1E
S18 S17
———
S19 S20
Jackson County 1974

From which:

Original BTs marked by Ives and Hyde in 1854 were found as follows:

- A White Oak, 20 ins. diam., with healed blazes, bears N8°E, 56.76 feet to estimated face of blaze. Record, N9°E, 56.76 feet.
- A White Oak, 23 ins. diam., containing chain notch and scribed "BT" in opened lower face, bears S14°E, 66.66 feet to scribed face. Record, S19°E, 66.66 feet.
- A White Oak, 23 ins. diam., with healed blazes, bears record, S37½°W, 49.50 feet to estimated face of blaze.
- A fork, 16 ins. diam., of a double Black Oak, (located on Northerly bearing fence line) with rotted upper face, bears record N10°W, 88.44 feet to said face.

I marked the following trees CS BT and take measurements to center of trees at lower blaze:

- A White Oak, 8 ins. diam., bears N57½°E, 35.57 feet.
- A White Oak, 8 ins. diam., bears S80°E, 30.8 feet.
- A White Oak, 7 ins. diam., bears S70°W, 28.15 feet.

March 12, 1974
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor