

## FIRST RE-ESTABLISHMENT

GCDB 200640

Quarter corner common to Sections 5 and 6, Township 36 South, Range 1 East, W.M.  $V = 20\frac{1}{2}^\circ$

From the following evidence and at the location described below, I set a 1 x 36 ins. G.I. pipe 24 ins. in the ground (in a found mound of stones) with a  $2\frac{1}{2}$  ins. bronze disc marked:

T36S R1E  
¼S  
6 | 5  
Jackson County 1974

Original BTs recorded by Ives and Hyde in 1854 found as follows:

- A White Oak, 23 ins. diam., containing scribe marks in opened upper face, bears record,  $N12^\circ E$ , 79.86 feet to estimated face of lower blaze.
- A sawed Pine stump about 38 ins. diam. bears record,  $S67^\circ W$ , 22.44 feet to estimated face of blaze.

I marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak, 15 ins. diam., bears  $N7\frac{1}{2}^\circ E$ , 38.7 feet.
- A White Oak, 12 ins. diam., bears  $N77^\circ W$ , 38.3 feet.

Corner lies on North-South fence line.

March 19, 1974  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor