

SECOND RE-ESTABLISHMENT

GCDB 240400

Quarter corner common to Sections 17 and 20, Township 36 South, Range 1 East, W.M. $V = 22\frac{1}{2}^\circ$

From the following evidence and at the location described below, I set a 1 x 36 ins. G.I. pipe 26 ins. in the ground with a 2½ ins. bronze disc marked:

T36S R1E
17
¼S —
20
Jackson County
1974

From which:

- An original BT marked by Ives and Hyde in 1854, now a White Oak, 8 ins. diam., containing partial scribed "B" in open rotted lower face, bears record, $S46^\circ E$, 73.26 feet to scribed face.
- At record location of original N.E. BT, $N35^\circ E$, 87.12 feet, a depression with rotted Oak alongside found
- No evidence found of a White Oak, recorded as 8 ins. diam. (August 23, 1887), bearing $S50^\circ E$, 104 lks., by Jas. Jeffrey, County Surveyor, in his "Record of U.S. Corners", page 9.

I mound stones around corner, marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak, 8 ins. diam., bears $N22^\circ E$, 71.9 feet.
- A White Oak, 7 ins. diam., bears $N76^\circ W$, 29.8 feet.

Corner lies at intersection of North-South and West fence line.

March 11, 1974
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor