

FIRST RE-ESTABLISHMENT

GCDB 300200

Section corner common to Sections 28, 29, 32 and 33, Township 36 South, Range 1 East, W.M.

At the corner, found 60d spike set in old mound of stone on (L. Moffit, ORLS 944) survey, in progress. Directly over said spike, set a 1 x 36 ins. galvanized iron pipe, 28 ins. in the ground, with a 2½ ins. diam. bronze cap marked:

JACKSON COUNTY 1984

T36S R1E

29	28
----	----

32	33
----	----

The single remaining original bearing tree recorded by Ives and Hyde in 1854,

- Now a partly burned White Oak stump shell 21 ins. diam. brs. Record: S64°E, 31.02 feet (on slope) to estimated face.

Mk new trees "CS-BT" and take measurements to center of trees at lower blaze:

- White Oak, 5 ins. diam., brs. N2½°E, 29.55 feet.
- Black Oak, 10 ins. diam., brs. S44½°E, 37.34 feet.
- White Oak, 6 ins. diam., brs. S45°W, 33.96 feet.
- White Oak, 6 ins. diam., brs. N85°W, 20.40 feet.

Corner lies on Southeast slope, 3½ feet North of East-West fence line. See also 1984 Jackson County field notes, page 90.

July 23, 1984
R. Frost
L. Moffit (ORLS 944)

Edward McGinty
County Surveyor

V = 20¾°

P. - 90