

**FIRST RE-ESTABLISHMENT
CORNER COMMON TO SECTIONS 4 AND 5 ONLY
GCDB 300700**

Standard Section Corner on the 8th Standard Parallel, Sections 4 and 5, Township 36 South, Range 1 East, W.M.

Found the original BT to Southeast with scribe visible. Stump holes for the Southwest and the Northwest BTs. The pointed rock ledge to the Northeast has disintegrated to the extent that no definite point for measurement could be determined. Also found the line tree to the East.

From which evidence set a 1 1/8" x 17" iron pin in loose rock for corner from which the original line tree now a 20" White Oak brs. East 42.3 feet.

- Scribe a 14" Yellow Pine CS-BT which brs. South 30°W, 27.9 feet.
- Scribe a 6" Black oak CS-BT which brs. North 28½°W, 23.0 feet.
- Scribe a 16" White Oak CS-BT which brs. South 72°E, 42.2 feet.

March 26, 1953
C. Z. Boyden
L. D. Pinkham
M. E. Boyden

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

**SECOND RE-ESTABLISHMENT
CORNER COMMON TO SECTIONS 4 AND 5 ONLY
GCDB 300700**

Standard Section corner common to Sections 4 and 5, Township 36 South, Range 1 East, W.M.

Found flush, the 1¹/₈ ins. x 17 ins. iron set on first re-establishment, page 9, in 1953. Replaced said pin with a 1 x 36 ins. galvanized iron pipe set 22 ins. in the ground. In the top of said pipe, set in concrete, a 2¹/₂ ins. diam. brass cap marked:

T36S R1E
S C
5 | 4
CS
1988

Original bearing tree marked by Ives and Hyde in 1854 found:

- Black Oak, approximately 40 ins. diam., down with chopped out and rotted faces, brs. Record: S25°E, 15.9 feet to approximate position of original face in stump hole.
- Original line tree recorded by Ives and Hyde, found White Oak, 23 ins. diam., brs. Record: East, 42.5 feet to center. Record distance; 43.56 feet.

Bearing trees marked on said first re-establishment found with double healed blazes and measured to center of trees at lower blaze:

- White Oak, now 18 ins. diam., brs. Record: S72°E, 42.2 feet.
- Ponderosa Pine, now 18 ins. diam., brs. S29¹/₂°W, 28.35 feet. Record; S30°W, 27.9 feet.
- Black Oak, now 11 ins. diam., brs. N27°W, 23.6 feet. Record; N28¹/₂°W, 23.0 feet.

The brass cap and iron pipe at the corner to Sections 32 and 33, T35S, R1E brs. S86°E, 71.6 feet. Record; East, 72.6 feet.

Corner lies on a rocky South slope, an estimated 70 feet South of the top of a level plateau, 1 feet North of an East-West fence and N78°E, 7.0 feet from a corner post to a fence bearing South.

February 24, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 18°
P. 65-66