

SPECIAL CORNER

FIRST RE-ESTABLISHMENT

GCDB 340100

Quarter corner common to Section 4, Township 37 South, Range I East and Section 33, Township 36 South, Range 1 East, W.M.

Found flush with top of 12 ins. high mound of stone, 5/8 ins. diam. rebar with yellow plastic cap marked "Moffit PLS 944", set on Survey No. 10043 dated 1984. Over top of found rebar, set a 1x36 ins. galvanized iron pipe (projects 6 ins. from mound of stone) with a 2 1/2 ins. diam. brass cap marked:

T36S R1E  
33  
1/4S ———  
4  
T37S

From which;

- White Oak, 13 ins. diam. with area of faces axed out, reported on Survey No. 10043 as "the original bearing tree...." brs. in accord with the original (1854) Record: N8°W, 80.42 feet to estimated face; re-measured 80.75 feet to center of tree near base.
- No evidence of the Northeast ("Bugwood") bearing tree found

To perpetuate this location,

- Marked a new tree "CS" "BT"; White Oak, 7 ins. diam., brs. N52°E, 42.0 feet to center of tree at lower blaze.

Corner lies in large opening near the top of ridge c. N45°E.

The middle of Yankee Creek reservoir, an estimated 1.5 miles distant, brs. N10°W.

January 20, 1987  
R. Frost  
T. Newcomb

Edward McGinty  
County Surveyor

V = 19 1/2°  
P.-16