

## FIRST RE-ESTABLISHMENT

GCDB 340400

Quarter corner common to Sections 16 and 21, Township 36 South, Range 1 East, W.M.  $V = 19\frac{3}{4}^\circ$

From the original evidence and at the location described below, I set a 1 x 36 ins. G.I. pipe 28 ins. in the ground with a  $2\frac{1}{2}$  ins. bronze disc marked:

T36S R1E  
16  
 $\frac{1}{4}$ S —  
21  
JACKSON COUNTY  
1974

Original BTs marked by Ives and Hyde in 1854 found as follows:

- A White Oak, 13 ins. diam., opened to expose scribed "B", bears  $S57^\circ E$ , 59.15 feet to center of tree at base. Record,  $S57^\circ E$ , 64.68 feet. (**Note:** This tree, 10 ins. diam., which scribed, now 13 ins. diam., contains 5 ins. of overgrowth at face.
- A partial shell of a White Oak stump, with section alongside containing reverse impression of a chaining notch and scribed "BT" bears record,  $N42^\circ W$ , 54.78 feet to blazed face.

I mound stones around corner and marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak, 6 ins. diam., bears  $S21\frac{1}{2}^\circ W$ , 16.6 feet.
- A White Oak, 11 ins. diam., bears  $N15\frac{1}{2}^\circ W$ , 34.9 feet.

February 27, 1974  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor