

**FIRST RE-ESTABLISHMENT
QUARTER CORNER TO SECTION 4 ONLY
GCDB 340700**

Quarter corner to Section 4 only. Eighth Standard Parallel.

From surveyed proportionate location

- I found a stump hole with Black Oak remains of original bearing tree recorded by Ives and Hyde in 1854, which bears South 7°00' West, 54.87 feet to approximate center. Original bearing tree record location; South 7°00' West, 54.12 feet.
- The stump hole with White Oak remains of recorded original line tree bears Record: West, 110.22 feet to approximate center.

I drive a 1 x 36 ins. G.I. pipe flush with the ground with a 2½ ins. bronze disc. stamped:

JACKSON COUNTY 1979
T35S
—
¼ S4
T36S R1E

I trench and place mound of stone around monument and drive a 6 foot red with white top steel fence post Southwest 1.0 feet from corner. I mark the following trees "CS-BT"; and take bearings and distances to center of trees at lower blaze:

- Ponderosa Pine, 17 ins. diam. bears South 72°02' West, 40.6 feet.
- White Oak, 9 ins. diam. bears North 0°50' West, 16.95 feet.
- Corner bears South 42 feet from east-west fence line and West, 24 feet from north-south fence line.
- The brass cap South one-quarter corner of Section 33, T35S R1E, bears North 89°57'52" East, 75.90 feet. (For basis of bearing refer to Note "A" on map of Jackson County Surveyor Job File No. 79-10).

Set by: J. Swanson & J. Gallegos
Evidence by: R. Frost
B. Malotte
May 9, 1979

Approved by: Edward McGinty
County Surveyor