

FIRST RE-ESTABLISHMENT

GCDB 400140

Quarter corner common to Sections 33 and 34, Township 36 South, Range 1 East, W.M.

At the corner, found 60d spike set on (L. Moffit, ORLS 944) survey, in progress. Directly over said spike, set a 1x24 ins. galvanized iron pipe, 12 ins. in the ground, with 2½ ins. diam. bronze cap marked:

JACKSON COUNTY 1984
T36S R1E
¼S
33 | 34

Original bearing trees recorded by Ives and Hyde in 1854 found as follows:

- White Oak stob, 14 ins. diam., area of faces axed out long ago, brs. Record: N57°E, 55.44 feet to estimated face. Re-measured 55.65 feet to center of tree.
- White Oak, 24 ins. diam., area of faces axed out long ago, brs. Record: S66°W, 47.52 feet to estimated face. Re-measured 48.14 feet to center of tree.

Mound stones around corner, mk. new trees "CS" "BT" and take measurements to center of trees at lower blaze:

- White Oak, 9 ins. diam., brs. S82°30'E, 54.15 feet.
- White Oak, 10 ins. diam., brs. S82°06'W, 56.85 feet.

Corner lies about 120 feet Southeast of road crossing crest of hill and 12 feet west of same road, N36°W.

July 23 1984
R. Frost
L. Moffit (ORLS 944)

Edward McGinty
County Surveyor

P. -91