

FIRST RE-ESTABLISHMENT

GCDB 400200

Section corner common to Sections 27, 28, 33, and 34, Township 36 South, Range 1 East, WM
V = 20°

From the following evidence and at the location described below I set a 1x36 ins. G.I. pipe 28 ins. in the ground with a 2½ ins. bronze disc marked:

T36S R1E		T36S R1E
S28		S27
S33		S34
C.S.		
1973		

Original BTs marked by Ives and Hyde in 1854 found as follows:

- A Black Oak, 15 ins. diam., with healed blaze bears N65°E, 54.12 feet to estimated face of blaze. Record, N64°E, 54.12 feet.
- The base of a double Black Oak, 15 ins. diam., with healed blaze, brs. record, S45°E, 3.3 feet to estimated face of blaze.
- A White Oak snag, 18 ins. diam., with healed blaze, bears record, S9½°W, 42.9 feet (on slope) to estimated face of blaze.
- A Laurel snag, approximately 14 ins. diam., in a cluster of Laurel, containing scribe marks including scribed "S" in exposed weathered face, bears record, N25°W, 33.0 feet to scribed face.

I mound stones around corner marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak, 5 ins. diam., bears N42½°E, 21.8 feet.
- A White Oak, 5 ins. diam., bears S60°E, 57.8 feet.
- A Laurel, 6 ins. diam., bears S81°W, 9.35 feet.
- A Ponderosa Pine, 10 ins. diam., bears N14°W, 66.1 feet.

Corner of East-West and Southerly bearing fence line is approximately 21 feet North.

December 31, 1973

B. Malotte
R. Frost
V. Gardener: Witness

Approved by: Edward McGinty
County Surveyor