

FIRST RE-ESTABLISHMENT

GCDB 400400

Section corner common to Sections 15, 16, 21, and 22, Township 36 South, Range 1 East, WM
 $V = 19\frac{1}{2}^\circ$

From the following evidence and at the location noted below, I set a 1x36 ins. G.I. pipe 30 ins. in the ground with a 2½ ins. bronze disc marked:

T36S R1E	
S16	S15

S21	S22
Jackson County	
1974	

BTs marked by Ives and Hyde in 1854 found as follows:

- The stump remains of a down and decayed Black Oak bears record, N36°E, 26.4 feet.
- A Black Oak snag, 18 ins. diam., with rotted upper face, bears record, S80°E, 21.78 feet to exposed face.
- A White Oak, 14 ins. diam., containing a scribed "2" and other marks in opened upper face, bears record, S27°W, 59.4 feet on slope, to scribed face. Re-measured 58.8 feet to center of tree.
- The base of a down and rotted Black Oak, approximately 36 ins. diam., located on Easterly-Westerly fence line, containing scribed "BT", bears record, N24°W, 38.94 feet.

I marked the following new trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak, 7 ins. diam., bears N30°E, 33.1 feet. **Note:** This tree has grown over old fence wire attached to it.
- A double Black Oak, bears S3°E, 40.7 feet.
- A White Oak, 11 ins. diam., bears S71°E, 46.4 feet.
- No suitable tree located in S.W. quadrant.
- A Black Oak, 7 ins. diam., bears N45°W, 34.66 feet.

March 21, 1974

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor