

FIRST RE-ESTABLISHMENT

GCDB 400440

Quarter corner to Sections 15 and 16, Township 36 South, Range 1 East, W.M.

Found the original witness tree to the Northwest with scribe visible.

From which evidence, set a 1" x 36" galvanized iron pipe with top 3" above the ground surface for corner from which:

- The original witness tree, now a 16" White Oak bears N42°W, 19.8 feet.
- A 12" Fir, scribed CS-BT, the center of which tree bears N74¾°W, 45.4 feet.
- A 10" Fir, scribed CS-BT, the center of which tree bears S19½°W 43.6 feet.

December 22, 1959

M. E. Boyden

F. A. Roberts

C. Charley, present

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 400440

Quarter corner common to Sections 15 and 16, Township 36 South, Range 1 East, W.M.

Found projecting 3 ins., the 1 ins. diam. iron pipe reported set on first re-establishment, page 11, in 1959. In the top of said pipe, set in concrete a 2½ ins. diam. brass cap marked:

T36S R1E
¼S
16 | 15
C.S.
1988

Original bearing tree marked by Ives and Hyde in 1854 found:

- White Oak, now a 17 ins. diam. shell with rotted out blazes brs. Record: N42°W, 19.8 feet to estimated face.

Bearing trees marked on said first re-establishment found with double healed blazes and measured to center of trees at lower blaze:

- Douglas Fir, now a 12 ins. diam. snag, brs. S19¼°W, 43.45 feet. Record; S19½°W, 43.6 feet.
- Douglas Fir, now a 12 ins. diam. snag, brs. N74½°W, 45.50 feet. Record; N74¾°W, 45.4 feet.

Scribe new trees "CS BT" and measure to center of tree at lower blaze:

- White Oak, 9 ins. diam. brs. N5¾°W, 74.7 feet.
- White Oak, 6 ins. diam. brs. S50¼°E, 33.45 feet.

Corner lies in Oak and Manzanita openings on a 20% S70°E slope, 40 feet Northwesterly from a North-South fence.

March 8, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 18½°
P. -75