

FIRST RE-ESTABLISHMENT

GCDB 400500

Corner common to Sections 9, 10, 15 and 16 Township 36 South, Range 1 East, W.M.

Set a 1" x 36" galvanized iron pipe with bronze cap stamped:

T. 36 S. R. 1 E.
9 | 10
Sec ——— Cor
16 | 15
C.S.
1970

7 inches in the ground for corner,

From which:

- The original bearing tree (now a 13" White Oak, plainly scribed "BT") bears S56°W, 60.1 feet to the face of the lower blaze;
- The original bearing tree (now a 22" Black Oak left intact) bears S½°E, 162.0 feet to the center of the tree;
- The original bearing tree (now a sawed Oak stump) bears N20½°E, 79.6 feet to the center;
- A stump hole agrees with the government record for the original Northwest bearing tree (N86°W, 103 feet).
- Scribed a 7" White Oak, "CS-BT" which bears S22°W, 82.1 feet to the face of the lower face;
- Scribed a 9" White Oak, "CS-BT" which bears N46½°W, 98.8 feet to the face of the lower blaze;
- Scribed a 12" Black Oak, "CS-BT" which bears 67°E, 88.8 feet to the face of the upper blaze.

January 22, 1970
F. Roberts, Deputy County Surveyor
Dan Phillips
Claus Charley, present