

FIRST RE-ESTABLISHMENT

GCDB 440500

Quarter corner common to Sections 10 and 15, Township 36 South, Range 1 East, WM $V = 10\frac{1}{2}^\circ$

Found original NW BT marked by Ives and Hyde in 1854, now a down Black Oak snag, containing reverse impression of scribed "B" in rotted lower face. At record bearing and distance, $N59^\circ W$, 46.86 feet from the base and stump hole of said tree.

I set a 1 x 36 ins. G.I. pipe 28 ins. in the ground, with a $2\frac{1}{2}$ ins. bronze disc marked:

T36S R1E
10
 $\frac{1}{4}S$ —
15
Jackson County 1974

I mound stones around corner, marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak, 10 ins. diam., bears $S56^\circ W$, 57.85 feet.
- A White Oak, 8 ins. diam., bears $N06\frac{1}{2}^\circ W$, 56.0 feet.
- A White Oak, 7 ins. diam., the corner of a North and Easterly-Westerly bearing fence lines, bears $S31^\circ W$, 6.3 feet.

Corner lies on W. edge of small irrigation ditch. About 160 feet West, a location marker is posted on a 6 ins. diam. White Oak, alongside the irrigation canal.

May 21, 1974

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor