

FIRST RE-ESTABLISHMENT

GCDB 500200

Section corner common to Sections 26, 27, 34, and 35, Township 36 South, Range 1 East, WM
 $V = 17\frac{1}{4}^\circ$

Found unrecorded 6x6 ins. concrete pedestal projecting 6 ins., with embedded 3½ ins. brass cap marked:

U.S. ENGINEER DEPARTMENT
Portland District
Boundary Monument

Original BTs marked by Ives and Hyde in 1854 found as follows:

- A White Oak snag, 17 ins. diam. with healed upper blaze, bears S34°E, 127.38 feet to estimated face of blaze. Record, S35°E, 127.38 feet.
- The base of a down and rotted White Oak, 9 ins. diam., containing reverse impression of scribed "BT", bears S16°W, 55.44 feet, on slope. Record, S18°W, 55.44 feet.
- The remains of a down and rotted White Oak, estimated diam., 12 ins., bears N27°W, 98.34 feet on slope. Record, N28°W, 98.34 feet.
- No evidence of N.E. BT found

I stamp additional information on found brass cap:

T36S R1E	
S27	S26
— —	
S34	S35
C.S.	
1974	

I marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak, 6 ins. diam., bears N61°E, 49.6 feet.
- A Ponderosa Pine, 10 ins. diam., bears S49°E, 43.5 feet.
- A Black Oak, 7 ins. diam., bears S22½°W, 60.5 feet.
- A Ponderosa Pine, 15 ins. diam., bears N19°W, 46.9 feet.

March 27, 1974

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor