

FIRST RE-ESTABLISHMENT

GCDB 500240

Quarter corner common to Sections 26 and 27, Township 36 South, Range 1 East, W.M.
 $V = 21\frac{1}{2}^\circ$

Found unrecorded 6x6 ins. concrete pedestal, projecting 6 ins. with embedded $3\frac{1}{2}$ ins. brass disc marked:

U.S. ENGINEER DEPARTMENT
Portland District
Boundary Monument

Original BTs marked by Ives and Hyde in 1854 found as follows:

- A Black Oak stump shell, 16 ins. diam., with rotted remains alongside containing reverse impression of scribed "S", "4" and other discernible scribe marks, bears $S50^\circ E$, 24.42 feet (on slope) to estimated face. Record, $S40^\circ E$, 24.42 feet.
- A White Oak snag, 18 ins. diam., approximately 20 feet high, with upper face chopped out, containing reverse impression of scribed "B" in rotted lower face, bears $S55\frac{1}{2}^\circ W$, 42.24 feet (on slope) to scribed face. Record, $S28^\circ W$, 42.24 feet (**Note:** Resultant discrepancies in bearings due to apparent erroneous entry in original record.)

I stamp additional information on found brass cap:

T36S R1E
¼S
27 | 26
C.S.
1974

I marked new trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak, 6 ins. diam., bears $S43\frac{1}{2}^\circ E$, 36.5 feet.
- A White Oak, 6 ins. diam., bears $S87^\circ W$, 26.0 feet.

Corner lies approximately $N83^\circ W$, 56 feet from a White Oak, 20 ins. diam., the corner of East and Northwest bearing fence lines.

March 27, 1974
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor