

FIRST RE-ESTABLISHMENT

GCDB 500300

Section corner to Sections 22, 23, 26 and 27, Township 36 South, Range 1 East, W.M.

Found the witness trees in Sections 22, 23, and 27 in place. The tree in Section 26 destroyed. The bearings and distances as given in the field notes do not check to a common point from the witness trees.

I find by setting a point according to the notes for the tree in Section 22, the other two trees will check for measurement. I therefore drove a ½" gas pipe for corner at the point above mentioned.

From which:

- The original BT in Section 23 bears N49°E, 59.4 feet.
- The original BT in Section 22 bears N66°W, 68.0 feet.
- The original BT in Section 27 bears S60°W, 139.3 feet.
- A new BT a 24" black oak bears S58½°E, 83.5 feet.

April 11, 1914
A. T. Brown, Deputy County Surveyor
H. Ling, Chainman
Philo Murphy, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500300

Section corner common to Sections 22, 23, 26 and 27, Township 36 South, Range 1 East, W.M.
V = 21°

Found in small spring branch, a 6 x 6 ins. concrete pedestal, projecting 6 ins., with imbedded 3½ ins. diam., brass cap marked:

U.S. ENGINEER DEPARTMENT
Portland District
Boundary Monument

BTs marked by Ives and Hyde in 1854, and noted by A.T. Brown on First re-establishment. (Page 2) in 1914 were found as follows:

- A White Oak, 14 ins. diam., with both faces rotted and/or burnt out, bears N49½°E, 57.5 feet to face of upper blaze. Distance on slope, 59.4 feet. Record, Ives and Hyde - N46°E, 59.4 feet A.T. Brown - N49°E, 59.4 feet.
- A White Oak snag, 14 ins. diam., 4 feet high, containing reverse impression of scribed "S" in rotted upper face, bears S60°W, 140.4 feet to scribed face. Record, Ives and Hyde - S58°W, 139.26 feet A.T. Brown - S60°W, 139.3 feet A BT added by A.T. Brown in 1914, now a Black Oak snag, 19 ins. diam., about 15 feet high, bears S58½°E, 83.5 feet to estimated face. Record, S58½°E, 83.5 feet.
- No evidence of Ives and Hyde's N.W. and S.E. BTs found Monument set by A.T. brown (½ ins. diam., gas pipe) was not found

I stamp additional information of afore-mentioned brass cap:

T36S R1E
S22 S23
———
S27 S26

I marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak 7 ins. diam., bears N31°E, 13.12 feet.
- A Black Oak, 9 ins. diam., bears S50½°E, 41.1 feet.
- A Black Oak, 6 ins. diam., bears S59½°W, 83.5 feet.
- A Black Oak, 7 ins. diam., bears N48°W, 29.6 feet.

February 25, 1974
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor