

FIRST RE-ESTABLISHMENT

GCDB 500440

Quarter corner to Sections 14 and 15, Township 36 South, Range 1 East, W.M.

Found old stake set for corner. Also found both Black Oak witness tree snags with scribe marks plain. One course and both distances check with the original government record.

From which evidence, set a 1" x 36" galvanized iron pipe with top 2" above the ground surface for corner,

From which:

- The original Black Oak (now 9" snag) bears N85°W, 27.7 feet.
- A 12" White Oak, scribed CS-BT, the center of which tree bears S75½°E, 40.3 feet.
- A 12" Black Oak, scribed CS-BT, the center of which tree bears S39½°W, 34.4 feet.

December 23, 1959
M.E. Boyden
F.A. Roberts
M. Despain

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500440

Quarter corner common to Sections 14 and 15, Township 36 South, Range 1 East, W.M.

Found projecting 2 ins., the 1 ins. diam. iron pipe reported set on first re-establishment, page 12, in 1959. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T36S R1E
¼S
15 | 14
C.S.
1988

Original bearing tree marked by Ives and Hyde in 1854 found:

- Oak stump remains, with axed, hollow portion alongside, brs. Record: N85°W, 27.95 feet to center of stump hole.

Bearing trees marked on first re-establishment found and measured to center of tree at lower blaze:

- White Oak, now 13 ins. diam. with scribed "CS" visible in partially healed upper face, brs. Record: S75½°E, 40.3 feet.
- Black Oak, now 13 ins. diam. with double healed blazes, brs. S39¾°W, 34.55 feet. Record; S39½°W, 34.4 feet.

Corner lies 2.4 feet East of a generally North-South fence, in Oak openings on a gentle North slope, an estimated 300 feet South of a Northwest-Southeast bearing dirt road.

March 8, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 17°

P. -74