

## FIRST RE-ESTABLISHMENT

GCDB 500500

Corner to Sections 10, 11, 14 and 15, Township 36 South, Range 1 East, W.M.

Found old sharpened oak stake for corner. Also found the original witness tree to the Northwest with scribe marks plain. Also found the stumps of the Northeast and Southeast witness trees and a stump hole for the Southwest witness tree.

It was found that the bearings to all trees checked favorably and the distance to all trees except the Northwest tree were in agreement with the original government record.

Therefore, replace the oak stake with a 2" x 27" galvanized iron pipe with the top 2" below the ground level for corner

From which:

- The center of the original witness tree, now a 36" Black Oak, bears N68°28'W, 115.5 feet.
- The center of a 36" Yellow Pine, scribed "CS-BT bears N37°04'E, 286.8 feet.
- The center of a 28" Black Oak, scribed CS-BT bears S39°16'W, 80.6 feet.

December 21, 1959  
M. E. Boyden  
F. A. Roberts  
C. Charley, present

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 500500

Section corner common to Sections 10, 11, 14 and 15, Township 36 South, Range 1 East, W.M.

Found 1 ins. deep, a 3/4 ins. diam. rebar of unknown origin. Over the top of said rebar, set a 1x36 ins. galvanized iron pipe 33 ins. in the ground. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T36S R1E	
10	11
— —	
15	14
C.S.	
1988	

Original bearing tree marked by Ives and Hyde in 1854 found:

- Black Oak, now 44 ins. diam. with concrete blocks cemented into face areas, brs. N68°33'W, 114.7 feet to center of tree at root crown.
- First re-establishment Record: N68°28'W, 115.5 feet to center.
- Original Record: N69°W, 116.16 feet to face.

Bearing trees marked on said first re-establishment, page 11, in 1959 found:

- Ponderosa Pine, now 37 ins. diam. with partial scribe marks visible in partially healed double blazes, brs. Record: N37°04'E, (base bearing), 287.8 feet to center of tree at lower blaze. Record; 286.8 feet to center.
- Black Oak, now 28 ins. diam. with double healed blazes, brs. S39°11'W, 80.4 feet to center of tree at lower blaze. Record; S39°16'W, 80.6 feet to center.

Take new reference as follows:

- The most easterly Northeast corner of a single story residence brs. S67°28'E, 88.89 feet.

Corner lies under a small ornamental Pine, about 35 feet North of the North side of a patio on a single story house.

March 16, 1988  
D. Edwards, Tech.  
T. Newcomb, Tech.

Edward McGinty  
County Surveyor

P. 97-98

SEE NEXT PAGE FOR CORNER NOTE

**CORNER NOTE**

**GCDB 500500**

Monument accidentally removed by land owner while landscaping. Found hole where pipe came from and reset a new monument, a 1 x 30 ins. diam. flanged iron pipe with attached brass cap marked :

T36S R1E	
10	11
-----	
15	14

Jackson County Surveyor

Protruding 1 in. above ground surface.

Bearing trees and references as recorded on Second Re-establishment.

July9, 1999  
T. Newcomb  
J. Burgess

Roger Roberts  
County Surveyor

P. -44