

FIRST RE-ESTABLISHMENT

GCDB 540600

Quarter corner common to Sections 2 and 11, Township 36 South, Range 1 East, W.M. $V = 19\frac{1}{2}^\circ$

From the following evidence and at the location noted below, I set a 1 x 36 ins. G.I. pipe 28 ins. in the ground with a 2½ ins. bronze disc. marked:

T36S R1E
2
¼S —
11
Jackson County 1974

Original BT`s marked by Ives and Hyde in 1854 found as follows:

- A Yellow Pine, 32 ins. diam., with healed blazes, bears record, $S44^\circ E$, 106.92 feet to estimated face of blaze. I re-blazed, scribe C.S. BT and measure 107.42 feet to center of tree.
- A hollow White Oak snag, 16 ins. diam., containing reverse impression of chaining notch and scribed "BT", bears $S82^\circ W$, 215.8 feet. Record, $S82^\circ W$, 247.50 feet.

I mound stones around corner and marked:

- A White Oak, 9 ins. diam., C.S. BT which bears, $N85^\circ W$, 83.75 feet to center of tree at lower blaze.

Original call to foot of ravine, 167 feet West of corner agrees favorably with re-established location.

March 20, 1974
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor